

Factorizations of the Thompson-Higman groups, and circuit complexity

Jean-Camille Birget *

February 2, 2008

Abstract

We consider the subgroup $lpG_{k,1}$ of length preserving elements of the Thompson-Higman group $G_{k,1}$ and we show that all elements of $G_{k,1}$ have a unique $lpG_{k,1} \cdot F_{k,1}$ factorization. This applies to the Thompson-Higman group $T_{k,1}$ as well. We show that $lpG_{k,1}$ is a “diagonal” direct limit of finite symmetric groups, and that $lpT_{k,1}$ is a k^∞ Prüfer group. We find an infinite generating set of $lpG_{k,1}$ which is related to reversible boolean circuits.

We further investigate connections between the Thompson-Higman groups, circuits, and complexity. We show that elements of $F_{k,1}$ cannot be one-way functions. We show that describing an element of $G_{k,1}$ by a generalized bijective circuit is equivalent to describing the element by a word over a certain infinite generating set of $G_{k,1}$; word length over these generators is equivalent to generalized bijective circuit size.

We give some coNP-completeness results for $G_{k,1}$ (e.g., the word problem when elements are given by circuits), and $\#P$ -completeness results (e.g., finding the $lpG_{k,1} \cdot F_{k,1}$ factorization of an element of $G_{k,1}$ given by a circuit).

1 Introduction

The Thompson groups, introduced by Richard J. Thompson [24, 20, 25], and their generalization by Graham Higman [16], are well known for their amazing properties and their importance in combinatorial group theory and topology. In this paper we focus on the computational role of these groups, continuing the work started in [2, 3], and we study some subgroups of the Thompson-Higman groups that are motivated by circuit complexity. We emphasize that we view the Thompson groups as *a model of computation* and not just a source of algorithmic problems. Indeed, since the Thompson group V has a faithful partial action on the set $\{0, 1\}^*$ of all bitstrings, it is natural to consider combinational circuits for computing elements of V ; i.e., we can view every element of V as the input-output function of an acyclic digital circuit (see [3]). The elements of V are bijections, hence we will see connections between V and *reversible computing*. More precisely, words over certain generating sets of V will be seen to be equivalent to circuits made of (generalized) bijective gates.

Combinational circuits have fixed-length inputs and fixed-length outputs, which is not the case for elements of V ; but the notion of a circuit can be adapted in order to be applied to the computation of elements of V . Moreover, for bijective circuits the fixed length of inputs and outputs implies that the circuit is length preserving. This leads to the question what the *length preserving* elements of V are, and how arbitrary elements of V are related to length preserving elements of V . The length preserving elements of V turn out to form an interesting subgroup, called lpV , and we will show that

*Supported by NSF grant CCR-0310793.

every element of V can be factored in a unique way as a product of an element of lpV and an element of the Thompson group F . This factorization carries over to the Thompson group T , where we have a unique $lpT \cdot F$ factorization. All of this generalizes to the Thompson-Higman groups $G_{k,1}$ and $T_{k,1}$.

The group $lpG_{k,1}$ is locally finite; it is a “diagonal” direct limit of finite symmetric groups, and it is simple when k is even; $lpT_{k,1}$ is a k^∞ Prüfer group. The connection with bijective (a.k.a. “reversible”) circuits leads to an interesting infinite generating set of lpV . We show that a description of an element of $G_{k,1}$ by a bijective circuit is equivalent to a description by a word over a certain infinite generating set of $G_{k,1}$; bijective circuit size is closely related to the word size over a certain infinite generating set of $G_{k,1}$. This shows that $G_{k,1}$ (and especially V) can serve as a model for bijective computing, with equivalent complexity.

We also investigate the computational complexity of some problems in $G_{k,1}$. We show that when an element $\varphi \in G_{k,1}$ is given by a bijective circuit (or by a general non-bijective circuit), the question whether φ is the identity, and the question whether φ is maximally extended, are coNP-complete problems; this is an application of [3] where $G_{k,1}$ and its connection with circuits was used to construct a finitely presented group with coNP-complete word problem. We show that elements of $F_{k,1}$ cannot be one-way functions, i.e., from a circuit for $f \in F_{k,1}$ one can easily find a circuit for f^{-1} . And we show that when $\varphi \in G_{k,1}$ is given by a bijective circuit, the problem of finding the $lpG_{k,1} \cdot F_{k,1}$ factorization of φ is #P-complete in general (and also under some restrictions).

Definition of the Thompson-Higman group

The rest of this Introduction consists of a brief, but complete, definition of the Thompson-Higman groups $G_{k,1}$, $T_{k,1}$, and $F_{k,1}$. We follow the exposition of [2, 3], based on partial actions on finite words, which simplifies the connections with circuits. Compare with the definition in [25] (based on infinite sequences), [16] (based on automorphisms of certain algebras), [22] (based on words and similar to this paper, but with different terminology), [9] (based on finite trees), [4] (based on piecewise linear maps between real numbers, see also [9]), [11] (related to associativity or commutativity in term rewriting, which was Thompson’s original view).

To define the Thompson-Higman group $G_{k,1}$ we fix an alphabet A of cardinality $|A| = k$. Let A^* denote the set of all finite *words* over A (i.e., all finite sequences of elements of A); this includes the empty word ε . The *length* of $w \in A^*$ is denoted by $|w|$; let A^n denote the set of words of length n . For two words $u, v \in A^*$ we denote their *concatenation* by uv or by $u \cdot v$; for sets $B, C \subseteq A^*$ the concatenation is $BC = \{uv : u \in B, v \in C\}$. A *right ideal* of A^* is a subset $R \subseteq A^*$ such that $RA^* \subseteq R$. A generating set of a right ideal R is a set C such that R is the intersection of all right ideals that contain C . A right ideal R is called *essential* iff R has a non-empty intersections with every right ideal of A^* . For words $u, v \in A^*$, we say that u is a *prefix* of v iff there exists $z \in A^*$ such that $uz = v$. A *prefix code* is a subset $C \subseteq A^*$ such that no element of C is a prefix of another element of C . A prefix code is *maximal* iff it is not a strict subset of another prefix code. One can prove that a right ideal R has a unique minimal (under inclusion) generating set, and that this minimal generating set is a prefix code; this prefix code is maximal iff R is an essential right ideal.

Partial functions on A^* will play a big role. For $f : A^* \rightarrow A^*$, let $\text{Dom}(f)$ denote the domain and let $\text{Im}(f)$ denote the image (range) of f . A *restriction* of f is any function $f_1 : A^* \rightarrow A^*$ such that $\text{Dom}(f_1) \subseteq \text{Dom}(f)$, and such that $f_1(x) = f(x)$ for all $x \in \text{Dom}(f_1)$. An *extension* of f is any function on A^* of which f is a restriction.

An *isomorphism* between right ideals R_1, R_2 of A^* is a bijection $\varphi : R_1 \rightarrow R_2$ such that for all $r_1 \in R_1$ and all $z \in A^*$: $\varphi(r_1 z) = \varphi(r_1) \cdot z$; the isomorphism φ can be described by a bijection between the prefix codes that minimally generate R_1 , respectively R_2 .

One can prove that an isomorphism φ between essential right ideals has a unique maximal extension (as an isomorphism between essential right ideals), denoted $\max \varphi$. So, $\max \varphi$ has no extension (other

than itself) to an isomorphism between essential right ideal.

Finally, the Thompson-Higman group $G_{k,1}$ is defined to consist of all maximally extended isomorphisms between finitely generated essential right ideals of A^* . The multiplication consists of composition followed by maximal extension: $\varphi \cdot \psi = \max(\varphi \circ \psi)$. Note that we let $G_{k,1}$ act partially and faithfully on A^* on the *left*.

Thompson and Higman proved that $G_{k,1}$ is finitely presented. Also, when k is even $G_{k,1}$ is simple, and when k is odd $G_{k,1}$ has a simple normal subgroup of index 2.

Every element $\varphi \in G_{k,1}$ can be described by a bijection between two finite maximal prefix codes; this bijection can be described concretely by a finite function *table*. When φ is described by a maximally extended isomorphism between essential right ideals, $\varphi : R_1 \rightarrow R_2$, we call the minimum generating set of R_1 the *domain code* of φ , denoted $\text{domC}(\varphi)$, and we call the minimum generating set of R_2 the *image code* of φ , denoted $\text{imC}(\varphi)$; because of the uniqueness of maximal extension, $\text{domC}(\varphi)$ and $\text{imC}(\varphi)$ are uniquely determined by φ . We call the cardinality $|\text{domC}(\varphi)| = |\text{imC}(\varphi)|$ the *table size* of φ , denoted $\|\varphi\|$. In [2] it was proved that for all $\varphi, \psi \in G_{k,1}$: $\|\varphi\psi\| \leq \|\varphi\| + \|\psi\|$. The concepts of $\text{domC}(\varphi)$, $\text{imC}(\varphi)$, *table*, and $\|\varphi\|$, can also be used when φ is not maximally extended.

For any finite generating set Γ of $G_{k,1}$ and any $\varphi \in G_{k,1}$, we define the *word length* of φ over Γ as the length of a shortest word over $\Gamma \cup \Gamma^{-1}$ that represents φ ; it is denoted by $|\varphi|_\Gamma$. In [2] it was proved that for any finite generating set Γ of $G_{k,1}$, the word length and the table size are closely related; for all $\varphi \in G_{k,1}$: $c' \|\varphi\| \leq |\varphi|_\Gamma \leq c \|\varphi\| \log_2 \|\varphi\|$ (for some constants $c, c' > 0$ depending on Γ but not on φ). Asymptotically, for most $\varphi \in G_{k,1}$ we also have $|\varphi|_\Gamma \geq c'' \|\varphi\| \log_2 \|\varphi\|$ (for some constant depending on Γ , $0 < c'' < c$). However, for $\varphi \in F_{k,1}$ it was proved in [9] that $c' \|\varphi\| \leq |\varphi|_\Gamma \leq c \|\varphi\|$.

We will use the well-known finitely presented subgroups $F_{k,1}$ and $T_{k,1}$ of $G_{k,1}$, introduced in [24] and [16]. The groups $F_{2,1}$ (also called F) and $T_{2,1}$ (also called T) have a large literature; a few examples are [20], [20, 25], [4], [9], [13], [7], [10], [5], [6], [14], [8]. Below we will introduce the subgroups $lpG_{k,1}$ and $lpT_{k,1}$ of length preserving elements of $G_{k,1}$, respectively $T_{k,1}$.

We will need the exact definition of $F_{k,1}$ and $T_{k,1}$ in the setting of partial actions on words (in A^*), and to do so we need some preliminary definitions. Assuming that a linear order has been chosen for the alphabet A , we can consider the dictionary order on A^* , denoted $\leq_d$, and defined as follows. For any $x_1, x_2 \in A^*$ we say that $x_1 \leq_d x_2$ (i.e., x_1 precedes x_2 in the dictionary order) iff either (1) x_1 is a prefix of x_2 , or, (2) letting p denote the longest common prefix of x_1 and x_2 , we have: $x_1 = pa_1v_1$, $x_2 = pa_2v_2$, with $a_1 < a_2$ (for some letters $a_1, a_2 \in A$, and words $v_1, v_2 \in A^*$, where $<$ is the strict order in A).

A partial map $f : A^* \rightarrow A^*$ is said to *preserve the dictionary order* iff for all $x_1, x_2 \in \text{Dom}(f)$ we have: $x_1 \leq_d x_2$ iff $f(x_1) \leq_d f(x_2)$.

We also want to define “cyclical preservation” of the dictionary order. Here we will simply write $<$ for $<_d$ (strict dictionary order). A cyclical order of a finite maximal prefix code $P \subset A^*$ is a listing $(x_0, x_1, \dots, x_{|P|-1})$ of all the elements of P such that for some integer s : $(x_s, \dots, x_{|P|-1}, x_0, \dots, x_{s-1})$ is the listing of P in dictionary order. In other words, a cyclical order of P is a cyclic permutation of the dictionary order on P .

We say that a partial map $f : A^* \rightarrow A^*$ *cyclically preserves the dictionary order* iff for all finite sequences $(x_0, x_1, \dots, x_{n-1})$ we have: $(x_0, x_1, \dots, x_{n-1})$ is a cyclical order of some finite maximal prefix code iff $(f(x_0), f(x_1), \dots, f(x_{n-1}))$ is a cyclical order of some finite maximal prefix code.

The groups $F_{k,1}$ and $T_{k,1}$ can be defined as follows, from the point of view of partial actions on finite words (see [2]).

Definition 1.1 Assume that a linear order has been chosen for the alphabet A , where $|A| = k$. Then $F_{k,1}$ consists of the elements of $G_{k,1}$ that preserve the dictionary order of A^* , and $T_{k,1}$ consists of the elements of $G_{k,1}$ that cyclically preserve the dictionary order of A^* .

Another view of $F_{k,1}$: The elements of $F_{k,1}$ can be given the following interpretation. First we define the concept of a rank function on a (partial) order structure $(S, \leq)$. The *rank* of an element $t \in S$ is

$$\text{rank}_S(t) = |\{x \in S : x < t\}|,$$

i.e., the number of elements that strictly precede t . Every element of $\varphi \in G_{k,1}$ can be represented (after appropriate restriction) by a bijective partial function $\varphi : A^* \rightarrow A^*$ such that $\text{imC}(\varphi) = A^n$ for some $n > 0$, and $\text{domC}(\varphi)$ is some finite maximal prefix code of cardinality k^n (where $|A| = k$). If we view the elements of A^n as the integers $\{0, 1, \dots, k^n - 1\}$ in base- k representation we have:

$F_{k,1}$ consists of all elements of $G_{k,1}$ that can be represented by rank functions
 $\text{rank}_P(\cdot) : P \rightarrow \{0, 1, \dots, k^n - 1\},$

where n ranges over the positive integers, and $P \subset A^*$ ranges over all maximal prefix codes of cardinality k^n . This point of view will help us later in proving that elements of $F_{k,1}$ can have high computational complexity, even when their domain code $\text{domC}(\varphi)$ has an easy membership problem (see Theorem 7.16).

Overview: This paper consists of the following parts:

Part 1 consists of sections 2, 3, and 4. We introduce the subgroup $lpG_{k,1}$ of length preserving elements of the Thompson-Higman group $G_{k,1}$, and we give the $lpG_{k,1} \cdot F_{k,1}$ factorization of $G_{k,1}$; we generalize this unique factorization to other subgroups of $G_{k,1}$.

Section 5 makes the transition from part 1 to part 2, by giving a connection between circuits and some properties of $lpG_{k,1}$.

Part 2 consists of sections 6 and 7. We study V as a model for reversible circuits. We also investigate the complexity of some problems: We show that elements of F cannot be one-way functions, and we show that finding the $lpV \cdot F$ factorization of an element of V given by a circuit is $\#P$ -complete.

2 The subgroups $lpG_{k,1}$ and $lpT_{k,1}$

The Thompson-Higman group $G_{k,1}$ contains all finite symmetric groups, and this inspires the definition of the subgroup $lpG_{k,1}$ of all length-preserving elements of $G_{k,1}$. We will denote $lpG_{2,1}$ also by lpV . Another motivation of lpV , which we will develop more later, is the computation of elements of V and lpV by digital circuits. Indeed, circuits traditionally have a fixed length for inputs and a fixed length for outputs (corresponding to fixed numbers of wires); for bijective functions this means length preservation.

Definition 2.1 *The subgroup of length-preserving elements of the Thompson-Higman group $G_{k,1}$ is $lpG_{k,1} = \{\varphi \in G_{k,1} : \forall x \in \text{Dom}(\varphi), |x| = |\varphi(x)|\}$. Similarly we define $lpT_{k,1} = T_{k,1} \cap lpG_{k,1}$.*

Restriction or extension of a length-preserving partial function $A^* \rightarrow A^*$, representing an element of $G_{k,1}$, is again length preserving, so $lpG_{k,1}$ is well-defined as a subset of the group $G_{k,1}$. The inverse of a length-preserving partial function is also length-preserving. After a restriction, if necessary, any finite set of elements of $lpG_{k,1}$ can be represented by permutations of the same set A^m , for any large enough m . Hence $lpG_{k,1}$ is closed under composition. It follows that $lpG_{k,1}$ is a subgroup of $G_{k,1}$. The group $lpG_{k,1}$ is *locally finite* (i.e., every finitely generated subgroup is finite), and $lpG_{k,1}$ contains all the finite symmetric groups $\mathfrak{S}_{A^n}$, for all $n \geq 1$.

Assume we restrict an element $\varphi \in lpG_{k,1}$ so that its domain and image codes are both A^m for some m . Then the additional overall restriction operation (which replaces each $\varphi(x) = y$ by the k -tuple $\varphi(xa) = ya$, where a ranges over A) leads to the following embeddings:

$$\otimes \text{id}_A : \pi \in \mathfrak{S}_{A^n} \hookrightarrow \pi \otimes \text{id}_A \in \mathfrak{S}_{A^{n+1}},$$

where for all $x \in A^n$ and $a \in A$ we define $(\pi \otimes \text{id}_A)(xa) = \pi(x) \cdot a$ (where $\cdot$ denotes concatenation). This type of embedding of symmetric groups is called *diagonal* [30], [15]. Moreover, when $|A| = k$ is *even* then the above embedding factors through the alternating group

$$\mathfrak{S}_{A^n} \hookrightarrow \mathfrak{A}_{A^{n+1}} \subset \mathfrak{S}_{A^{n+1}}.$$

Indeed we have the following generalization of an observation of [23] (see also Section 5 below): For any positive integer n and any $\pi \in \mathfrak{S}_{A^n}$, the permutation $\pi \otimes \text{id}_A$ is *even*. Indeed, the transformation $\pi \rightarrow \pi \otimes \text{id}_A$ replaces one transposition $(u|v)$ of π (with $u, v \in A^n$) by the sequence of transpositions $(ua_1|va_1) \dots (ua_k|va_k)$, i.e., k transpositions with k even; here $A = \{a_1, \dots, a_k\}$.

The above embeddings yield the following.

Proposition 2.2 *The group $lpG_{k,1}$ is isomorphic to the direct limit of the sequence of diagonal embeddings $\otimes \text{id}_A : \mathfrak{S}_{A^n} \hookrightarrow \mathfrak{S}_{A^{n+1}}$.*

When $|A| = k$ is even, $lpG_{k,1}$ is isomorphic to the direct limit of the sequence of embeddings $\mathfrak{S}_{A^n} \hookrightarrow \mathfrak{A}_{A^{n+1}} \subset \mathfrak{S}_{A^{n+1}}$.

These are examples of the direct limits of symmetric groups considered in [17], chapter 6, and in [15], section 1.5. The embedding maps are of “diagonal” type, in the terminology of these references. By these references we also conclude that when k is even, $lpG_{k,1}$ is a simple group, and when k is odd, $lpG_{k,1}$ has a simple subgroup of index 2 (via the parity map). In any case, it also follows from [17] and [15] that $lpG_{k,1}$ is different from the finitary symmetric group and the finitary alternating group; indeed, the finitary symmetric group does not contain any Prüfer groups, whereas $lpG_{k,1}$ contains $lpT_{k,1}$ which is a group of Prüfer type (as we shall see next). However, $lpG_{k,1}$ also contains many copies of the finitary symmetric group (as was mentioned in [25]).

The observations above apply also to the Thompson group $T_{k,1}$. Let us denote by $\mathbb{Z}_{A^n}$ the cyclic subgroup of $\mathfrak{S}_{A^n}$ generated by the permutation $w_i \mapsto w_{(i+1) \bmod k^n}$, where $(w_i : i = 0, 1, \dots, k^n - 1)$ is the listing of A^n in dictionary order. $\mathbb{Z}_{A^n}$ consists of the elements of $\mathfrak{S}_{A^n}$ that cyclically preserve the dictionary order. Just as for the symmetric groups on A^n , the restriction operation of $G_{k,1}$ gives an embedding of $\mathbb{Z}_{A^n}$ into $\mathbb{Z}_{A^{n+1}}$, by the transformation $\otimes \text{id}_A$ which sends the generator $(w_i \mapsto w_{(i+1) \bmod k^n})$ of $\mathbb{Z}_{A^n}$ to the element $(v_j \mapsto v_{(j+k) \bmod k^{n+1}})$ of $\mathbb{Z}_{A^{n+1}}$. Here, $(v_j : j = 0, 1, \dots, k^{n+1} - 1)$ is the listing of A^{n+1} in dictionary order. Thus we have:

Proposition 2.3 *The group $lpT_{k,1}$ is isomorphic to the k^∞ Prüfer group, given by the direct limit of the sequence of embeddings $\mathbb{Z}_{A^n} \hookrightarrow \mathbb{Z}_{A^{n+1}}$, where the embeddings are determined by the restriction operation of $G_{k,1}$.*

The k^∞ Prüfer group is isomorphic to the multiplicative group of the complex k^n th roots of unity (for all $n > 0$), or the additive group of k -ary rationals modulo 1, i.e., $\{\frac{m}{k^n} \bmod 1 : n, m \in \mathbb{N}\}$.

3 Length-preserving order-preserving factorization of $G_{k,1}$ and $T_{k,1}$

Let $\mathbf{1}$ denote the identity of $G_{k,1}$.

Lemma 3.1 *If an element of $F_{k,1}$ has a representation $f : A^* \rightarrow A^*$ such that $\text{dom}C(f) = \text{im}C(f)$ then f represents the identity. Hence, $F_{k,1} \cap lpG_{k,1} = \{\mathbf{1}\}$.*

Proof. Since $\text{dom}C(f) = \text{im}C(f)$, f is a permutation of $\text{dom}C(f)$. For any finite set of words, the only permutation that preserves the dictionary order is the identity.

We saw already that every element $\varphi \in lpG_{k,1}$ can be represented by a permutation of A^m for some $m > 0$, so $\text{dom}C(\varphi) = \text{im}C(\varphi)$ for every $\varphi \in lpG_{k,1}$. $\square$

Theorem 3.2 .

- We have $G_{k,1} = lpG_{k,1} \cdot F_{k,1}$ where every element φ of $G_{k,1}$ has a unique factorization $\varphi = \pi \cdot f$ with $\pi \in lpG_{k,1}$ and $f \in F_{k,1}$.
- Symmetrically there is a unique factorization $G_{k,1} = F_{k,1} \cdot lpG_{k,1}$.
- For $T_{k,1}$ there are unique factorizations $T_{k,1} = lpT_{k,1} \cdot F_{k,1} = F_{k,1} \cdot lpT_{k,1}$.

Proof. Uniqueness of the factorization follows immediately from Lemma 3.1: If $\pi_1 f_1 = \pi_2 f_2$ then $\pi_2^{-1} \pi_1 = f_2 f_1^{-1} \in F_{k,1} \cap lpG_{k,1} = \{\mathbf{1}\}$, hence $\pi_2^{-1} \pi_1 = \mathbf{1} = f_2 f_1^{-1}$. Existence follows from the following factorization algorithm, whose input is any $\varphi \in G_{k,1}$.

Factorization algorithm:

- (1) Restrict φ so that its image code becomes A^n for some $n > 0$. Let P be the corresponding domain code (of cardinality k^n). So now φ is represented by a bijection $P \rightarrow A^n$.
- (2) Let $f : P \rightarrow A^n$ be the unique element of $F_{k,1}$ determined by the finite maximal prefix codes P and A^n .
- (3) Let $\pi(\cdot) = \varphi f^{-1}(\cdot)$; then $\varphi = \pi f$. [End of algorithm.]

We claim that $\pi \in lpG_{k,1}$. Indeed, the domain code and the image code of π are both A^n ; hence π preserves length.

In the case of $T_{k,1}$ we observe that if $\varphi \in T_{k,1}$ then the unique factorization $\varphi = \pi f$ yields $\pi = \varphi f^{-1} \in T_{k,1}$ (since $\varphi \in T_{k,1}$ and $F_{k,1} \subset T_{k,1}$). $\square$

Observe that $f \in F_{k,1}$, produced by the factorization algorithm, is the ranking function of P , when we view A^n as the integers $\{0, 1, \dots, k^n - 1\}$ in base- k notation.

We will examine how the table sizes of $\pi \in lpG_{k,1}$ and $f \in F_{k,1}$ are related to the table size of φ when $\varphi = \pi f$. It turns out that π and f can have exponentially larger size than φ . In a later section we'll consider other complexity measures for π and f .

Proposition 3.3 *For all $n > 2$ there are elements $\varphi_n \in T_{2,1}$ whose factorization $\varphi_n = \pi_n f_n$ leads to an exponential increase in table size. More precisely, φ_n can be found so that $\|\varphi_n\| = n$, and $\|\pi_n\| = \|f_n\| = 2^{n-1}$.*

Proof. Let us pick $\varphi_n \in T_{2,1}$ given by the following table, over the alphabet $A = \{a, b\}$:

$$\varphi_n = \begin{bmatrix} a^{n-1} & a^{n-2}b & \dots & a^i b & \dots & a^2 b & ab & b \\ a^{n-2}b & a^{n-3}b & \dots & a^{i-1}b & \dots & ab & b & a^{n-1} \end{bmatrix}$$

So, φ_n is a cyclic permutation of the finite maximal prefix code $\{a^{n-1}\} \cup \{a^i b : i = n-2, \dots, 1, 0\}$. One observes that φ_n is reduced (unextendable) as given by the table, hence $\|\varphi_n\| = n$.

The longest words in the image code of φ_n in the above table have length $n-1$. When we restrict φ_n and let its image code become $\{a, b\}^{n-1}$ we obtain the following table of size 2^{n-1} for φ_n , where x_j ranges over $\{a, b\}^j$ (for $j = 1, \dots, n-2$):

$$\varphi_n = \begin{bmatrix} a^{n-1} & a^{n-2}bx_1 & \dots & a^i bx_{n-i-1} & \dots & a^2 bx_{n-3} & abx_{n-2} & b \\ a^{n-2}b & a^{n-3}bx_1 & \dots & a^{i-1}bx_{n-i-1} & \dots & abx_{n-3} & bx_{n-2} & a^{n-1} \end{bmatrix}$$

Then in the factorization $\varphi_n(\cdot) = \pi_n f_n(\cdot)$ we have:

$$f_n = \begin{bmatrix} a^{n-1} & a^{n-2}ba & a^{n-2}bb & \dots & a^i b a^{n-i-1} & a^i b s(x_{n-i-1}) & a^{i-1} b a^{n-i} & \dots \\ a^{n-1} & a^{n-2}b & a^{n-3}ba & \dots & a^i b b^{n-i-2} & a^{i-1} b x_{n-i-1} & a^{i-1} b b^{n-i-1} & \dots \\ \dots & a^2 b a^{n-3} & a^2 b s(x_{n-3}) & ab a^{n-2} & ab s(x_{n-2}) & b & & \\ \dots & a^2 b b^{n-4} & ab x_{n-3} & b b^{n-3} & b x_{n-2} & b^{n-1} & & \end{bmatrix}$$

where each x_j ranges over $\{a, b\}^j - \{b^j\}$, and where $s(x_j)$ denotes the *successor* of x_j in the dictionary order; hence, $s(x_j)$ ranges over $\{a, b\}^j - \{a^j\}$. In the table, the strings x_j and the strings $s(x_j)$ appear in dictionary order. We also have

$$\pi_n = \begin{bmatrix} b^{n-1} & a^{n-1} & a^{n-2}b & a^{n-3}ba & \dots & a^i b b^{n-i-2} & a^{i-1} b x_{n-i-1} & \dots \\ a^{n-1} & a^{n-2}b & a^{n-3}ba & a^{n-3}bb & \dots & a^{i-1} b a^{n-i-1} & a^{i-1} b s(x_{n-i-1}) & \dots \\ \dots & a^2 b b^{n-4} & a^2 b x_{n-3} & ab b^{n-3} & b x_{n-2} & & & \\ \dots & ab a^{n-3} & ab s(x_{n-3}) & b a^{n-2} & b s(x_{n-2}) & & & \end{bmatrix}$$

where the words x_j and $s(x_j)$ range over the same values and have the same meaning as for f_n .

One sees in the table of π_n that for every argument x , $\pi_n(x)$ differs from x in the right-most letter: whenever x ends in a , $\pi_n(x)$ ends in b , and vice versa. Hence, π_n as given by the table, is reduced (cannot be extended). Hence, $\|\pi_n\|$ is the size of the above table, i.e., 2^{n-1} . Similarly, in the table for f_n , x and $f_n(x)$ differ in the right-most letter, except when $x = a^{n-1}$ or $x = b$. Hence f_n as given by the table is reduced, and $\|f_n\| = 2^{n-1}$. $\square$

4 Other factorizations of $G_{k,1}$ and $T_{k,1}$

We will give an infinite collection of torsion subgroups S of $G_{k,1}$ that can be used for factoring $G_{k,1}$ as $S \cdot F_{k,1}$.

If $P \subset A^*$ is a finite maximal prefix code then for every $n \geq 0$, the overall restriction operation in $G_{k,1}$ determines a diagonal embedding

$$\otimes \text{id}_A : \pi \in \mathfrak{S}_{PA^n} \hookrightarrow \pi \otimes \text{id}_A \in \mathfrak{S}_{PA^{n+1}}$$

where $(\pi \otimes \text{id}_A)(xa) = \pi(x) \cdot a$, for all $x \in PA^n$, $a \in A$. This is a generalization of the embedding $\mathfrak{S}_{A^n} \hookrightarrow \mathfrak{S}_{A^{n+1}}$ that we saw earlier (which was the special case when P consists of just the empty word). We then take the direct limit of this sequence of symmetric groups and obtain a subgroup of $G_{k,1}$, denoted by

$$\bigcup_{n \geq 1} \mathfrak{S}_{PA^n}.$$

Just as for $lpG_{k,1}$, when $k = |A|$ is even the group $\bigcup_{n \geq 1} \mathfrak{S}_{PA^n}$ is simple, and when k is odd the group has a simple subgroup of index 2 (via the parity map).

Theorem 4.1 *If $P \subset A^*$ is a finite maximal prefix code then $S = \bigcup_{n \geq 1} \mathfrak{S}_{PA^n}$ is a subgroup of $G_{k,1}$, and we have $G_{k,1} = S \cdot F_{k,1}$. Moreover, $S \cap F_{k,1} = \{1\}$, hence we have a unique factorization.*

The group $T_{k,1}$ has the subgroup $Z = \bigcup_{n \geq 1} \mathbb{Z}_{PA^n}$ and we have $T_{k,1} = Z \cdot F_{k,1}$, with unique factorization for every element of $T_{k,1}$.

Proof. Every element φ of $\mathfrak{S}_{PA^n}$, as an element of $G_{k,1}$, has finite domain and image codes that are the same: $\text{domC}(\varphi) = \text{imC}(\varphi)$. Hence by Lemma 3.1, if $\varphi \in F_{k,1}$ then $\varphi = \mathbf{1}$. Hence, $S \cap F_{k,1} = \{\mathbf{1}\}$, which implies uniqueness of the factorization as we saw in the beginning of the proof of Theorem 3.2.

To prove existence of the factorization we use the same factorization algorithm as in the proof of Theorem 3.2. Let $\varphi' : P_1 \rightarrow Q_1$ represent any element of $G_{k,1}$, where P_1 and Q_1 are finite maximal prefix codes. Then by restriction we obtain a representation of the same element of the form $\varphi : P_2 \rightarrow PA^n$, where it suffices to choose n such that $PA^n A^* \subseteq Q_1 A^*$; since P and Q_1 are finite maximal prefix codes, such an n exists. The remainder of the proof follows from the same idea as for Theorem 3.2. We let $f : P_2 \rightarrow PA^n$ be the (unique) element of $F_{k,1}$ determined by the finite maximal prefix codes P_2 and PA^n , and let $\pi = \varphi f^{-1}$; then $\text{domC}(\pi) = \text{imC}(\pi) = PA^n$, hence $\pi \in \mathfrak{S}_{PA^n}$.

When $\varphi \in T_{k,1}$ the unique factorization $\varphi = \pi f$ satisfies $\pi = \varphi f^{-1} \in T_{k,1}$ (since $F_{k,1} \subset T_{k,1}$), hence $\pi \in T_{k,1} \cap S = Z$. $\square$

Higman (in [16], Section 6) shows that the question whether a given element of $G_{k,1}$ has finite order, is decidable. The following theorem shows that every element of finite order of $G_{k,1}$ belongs to some subgroup $\mathfrak{S}_P$, for some finite maximal prefix code P . Note that $\text{domC}(\varphi) = \text{imC}(\varphi) = P$ iff $\varphi \in \mathfrak{S}_P$.

Theorem 4.2 *Let $\Phi \in G_{k,1}$. Then Φ has finite order iff for some restriction φ of Φ we have $\text{domC}(\varphi) = \text{imC}(\varphi)$.*

Proof. If $\text{domC}(\varphi) = \text{imC}(\varphi) = P$ then $\varphi \in \mathfrak{S}_P$, hence φ has finite order.

Conversely, suppose that Φ is of finite order r , i.e., $\Phi^r(\cdot) = \text{id}(\cdot)$ with $r > 0$, and $\Phi^i(\cdot) \neq \text{id}(\cdot)$ for $0 \leq i < r$. By sufficiently restricting Φ we obtain maximal finite prefix codes $P_0, P_1, \dots, P_r \subset A^*$ such that for some restriction $\varphi : A^* \rightarrow A^*$ of Φ we have $P_0 \xrightarrow{\varphi} P_1 \xrightarrow{\varphi} \dots \xrightarrow{\varphi} P_{r-1} \xrightarrow{\varphi} P_r$, and $\varphi(P_i) = P_{i+1}$ for $i = 0, 1, \dots, r-1$. Since $\varphi^r(\cdot) = \text{id}(\cdot)$ it follows that $P_0 = P_r$.

Claim: For every $x \in P_0$, $C_x = \{\varphi^i(x) : i = 0, 1, \dots, r-1\}$ is a prefix code.

(Note: We only claim that no two $\varphi^i(x)$ are strict prefixes of each other; we do not rule out that $\varphi^i(x) = \varphi^j(x)$ for some $0 \leq i \neq j < r$.)

Proof of the Claim. If, by contradiction, we have $\varphi^\ell(x) = xz$, for a non-empty word $z \in A^*$ and $x \in P_0$, then for all $m \geq 0$ we have: $\varphi^{m\ell}(x) = xz^m$. This implies that $\bigcup_{\ell=0}^{r-1} P_\ell$ contains words of arbitrarily large length, which contradicts the fact that the prefix codes P_ℓ are finite.

It follows that when $i > j$ then $\varphi^j(x) \in P_j$ cannot be a strict prefix of $\varphi^i(x)$, since applying φ^{-j} to $\varphi^i(x) = \varphi^j(x)z$ yields $\varphi^{i-j}(x) = xz$.

Similarly, if we have $\varphi^i(x) = \varphi^j(x)z$ for a non-empty word $z \in A^*$ and $x \in P_0$ and if $i < j$ then, applying φ^{r-j} yields $\varphi^{r+i-j}(x) = xz$, and the reasoning in the first paragraph (with $\ell = r + i - j$) again yields a contradiction. We conclude that $\varphi^i(x)$ and $\varphi^j(x)$ cannot be strict prefixes of each other. [End, Proof of Claim.]

The Claim implies that $\varphi(C_x) = C_x$ and that C_x is a cycle of φ . For each $x \in P_0$ we have a cycle C_x as above. For different $x \in P_0$ the corresponding cycles yield either the same set or disjoint sets, i.e., for each $x, y \in P_0$, either $C_x = C_y$ or $C_x \cap C_y = \emptyset$. So, P_0 is partitioned into cycles of φ , hence $\varphi(P_0) = P_0$. $\square$

As a consequence of Theorem 4.2 and Lemma 3.1 we recover a result of Brin and Squier [4]:

Corollary 4.3 *The group $F_{k,1}$ is torsion-free.*

Theorem 4.4 *If $P_1, P_2 \subset A^*$ are finite maximal prefix codes let $S_i = \bigcup_{n \geq 0} \mathfrak{S}_{P_i A^n}$ for $i = 1$ or 2 . We have:*

$$S_1 = S_2 \text{ iff } \{P_1 A^n : n \geq 0\} \cap \{P_2 A^m : m \geq 0\} \neq \emptyset,$$

When $S_1 \neq S_2$, the subgroup generated by $S_1 \cup S_2$ contains infinitely many elements of $F_{k,1}$.

Proof. If $P_1 A^N = P_2 A^M$ for some $M, N \geq 0$ then $S_1 = \bigcup_{n \geq 0} \mathfrak{S}_{P_1 A^n} = \bigcup_{n \geq 0} \mathfrak{S}_{P_1 A^N A^n}$, since $\mathfrak{S}_{P_1 A^i} \hookrightarrow \mathfrak{S}_{P_1 A^N}$ when $i \leq N$. Similarly, $\bigcup_{m \geq 0} \mathfrak{S}_{P_2 A^M A^n} = S_2$. Now, since $P_1 A^N = P_2 A^M$ we have $\bigcup_{n \geq 0} \mathfrak{S}_{P_1 A^N A^n} = \bigcup_{m \geq 0} \mathfrak{S}_{P_2 A^M A^n}$, hence $S_1 = S_2$.

In the other direction, under the condition $\{P_1 A^n : n \geq 0\} \cap \{P_2 A^m : m \geq 0\} = \emptyset$ we will prove that the subgroup of $G_{k,1}$ generated by S_1 and S_2 together contains some non-identity elements of $F_{k,1}$. Since S_1 and S_2 are torsion groups whereas $F_{k,1}$ is torsion-free, this implies that $S_1 \neq S_2$.

Claim. There exist $n_0, m_0 \geq 0$ such that $P_1 A^{n_0} \cap P_2 A^{m_0} \neq \emptyset$, and $P_1 A^{n_0} \neq P_2 A^{m_0}$. Moreover, there are $v_1 \in P_1 A^{n_0} - P_2 A^{m_0}$ and $v_2 \in P_2 A^{m_0} - P_1 A^{n_0}$ such that v_1 is a strict prefix of v_2 .

Proof of the Claim: First, since each P_1 is a finite maximal prefix code, every long enough word belongs to $P_1 A^*$; e.g., every word $w \in A^*$ of length $\geq \max\{|p| : p \in P_1\}$ belongs to $P_1 A^*$. Therefore, for all m large enough (e.g., all $m \geq \max\{|p| : p \in P_1\}$) we have $P_2 A^m \subseteq P_1 A^*$. Let $m_0 \geq 0$ be such that $P_2 A^{m_0} \subseteq P_1 A^*$, and let us consider the possible $n \geq 0$ such that $P_2 A^{m_0} \subseteq P_1 A^n A^*$. For every $p_2 u \in P_2 A^{m_0}$ there exists exactly one $p_1 v \in P_1 A^n$ such that $p_1 v$ is a prefix of $p_2 u$. If $p_1 v \neq p_2 u$, we can increase the length of v (i.e., increase n) to move $p_1 v$ closer to $p_2 u$, until $p_1 v = p_2 u$. Thus, there exists n_0 such that $P_1 A^{n_0} \cap P_2 A^{m_0} \neq \emptyset$.

Finally, $P_1 A^{n_0} \neq P_2 A^{m_0}$ by the hypothesis that $\{P_1 A^n : n \geq 0\} \cap \{P_2 A^m : m \geq 0\} = \emptyset$. Since $P_1 A^{n_0} \neq P_2 A^{m_0}$ and since $P_1 A^{n_0}$ and $P_2 A^{m_0}$ are finite maximal prefix codes, $P_1 A^{n_0}$ and $P_2 A^{m_0}$ are not strict subsets of each other. Hence there exist $w_1 \in P_1 A^{n_0} - P_2 A^{m_0}$ and $v_2 \in P_2 A^{m_0} - P_1 A^{n_0}$. Moreover, since $P_2 A^{m_0} \subseteq P_1 A^{n_0} A^*$ we have: For any $v_2 \in P_2 A^{m_0}$ there exists $v_1 \in P_1 A^{n_0}$ such that v_1 is a prefix of v_2 . Since $v_2 \notin P_1 A^{n_0}$, v_1 is a strict prefix of v_2 . [This proves the Claim.]

We will now construct an element $\gamma_1 \in S_1$ whose $S_2 \cdot F_{k,1}$ factorization is of the form $\gamma_1 = \pi_2 f$ with $f \neq 1$. From this we obtain two elements $\gamma_1 \in S_1$ and $\pi_2 \in S_2$ such that $\pi_2^{-1} \gamma_1 = f \in F_{k,1}$ with $f \neq 1$.

Since $P_1 A^{n_0} \cap P_2 A^{m_0} \neq \emptyset$, there is $u_1 \in P_1 A^{n_0} \cap P_2 A^{m_0}$. Using u_1 and the words v_1 and v_2 from the Claim, we now define $\gamma_1 = (u_1 | v_1)$; i.e., γ_1 is the permutation of $P_1 A^{n_0}$ that transposes the two words u_1 and v_1 , and fixes the rest of $P_1 A^{n_0}$.

By Theorem 4.1, $\gamma_1 = \pi_2 f$ for a unique $\pi_2 \in S_2$ and $f \in F_{k,1}$. The factorization algorithm given in the proof of Theorem 4.1 finds π_2 and f by restricting γ_1 so that its image code becomes $\text{imC}(\gamma_1) = P_2 A^{m_0}$; the image codes of f and of π_2 (not necessarily maximally extended), as well as the domain code of π_2 , will also be $P_2 A^{m_0}$. The table of γ_1 is

$$\gamma_1 = \begin{bmatrix} u_1 & v_1 & \text{identity on} \\ v_1 & u_1 & P_1 A^{n_0} - \{u_1, v_1\} \end{bmatrix}.$$

By restricting so as to make $\text{imC}(\gamma_1) = P_2 A^{m_0}$ we obtain a table of the form

$$\gamma_1 = \begin{bmatrix} \dots & u_1 z & \dots & v_1 & \dots \\ \dots & v_1 z (= v_2) & \dots & u_1 & \dots \end{bmatrix}.$$

Here $z \in A^*$ is such that $v_2 = v_1 z$ and z is non-empty (recall that v_1 is a strict prefix of v_2). Hence for this restriction of γ_1, π_2 and f we have: $\text{domC}(\gamma_1) = \text{domC}(f)$ contains $u_1 z$. But since $u_1 \in P_2 A^{m_0}$ and since $P_2 A^{m_0}$ is a prefix code we find that $u_1 z \notin P_2 A^{m_0} = \text{imC}(f)$. Hence, $\text{domC}(f) \neq \text{imC}(f)$, therefore f is not the identity. Since $F_{k,1}$ is torsion-free, the conclusion follows. $\square$

Theorem 4.5 If $P_1, P_2 \subset A^*$ are finite maximal prefix codes let $S_i = \bigcup_{n \geq 0} \mathfrak{S}_{P_i A^n}$ for $i = 1$ or 2 . If $|P_1 A^N| = |P_2 A^M|$ for some $N, M \geq 0$ then as subgroups of $G_{k,1}$, $S_1 = \theta^{-1} S_2 \theta$ for some $\theta \in F_{k,1}$.

Proof. Let θ be the element of $F_{k,1}$ such that $\theta : P_1 A^N \rightarrow P_2 A^M$; then θ can be restricted such that $\theta : P_1 A^N A^n \rightarrow P_2 A^M A^n$ for all $n \geq 0$. Then as subgroups of $G_{k,1}$, $S_1 = \theta^{-1} S_2 \theta$. $\square$

Element-specific factorizations

For any element $\varphi \in G_{k,1}$ with $\text{domC}(\varphi) = P$ and $\text{imC}(\varphi) = Q$ we can apply Theorem 4.1 to obtain the factorizations $\varphi(\cdot) = \pi_Q f(\cdot) = f \pi_P(\cdot)$, where $f : P \rightarrow Q$ belongs to $F_{k,1}$, $\pi_Q \in \mathfrak{S}_Q$ and $\pi_P \in \mathfrak{S}_P$. Moreover, $\mathfrak{S}_P = f^{-1} \mathfrak{S}_Q f$. Note that in this factorization, $\|f\|, \|\pi_Q\|, \|\pi_P\| \leq \|\varphi\|$.

If $\varphi, \psi \in G_{k,1}$ are such that $\text{domC}(\varphi) = P$, $\text{imC}(\varphi) = Q = \text{domC}(\psi)$, and $\text{imC}(\psi) = R$, then (since domain and ranges match) we have the following multiplication formula for the factorization of $\psi \varphi(\cdot)$. If $\varphi(\cdot) = \pi_Q^\varphi f^\varphi$ and $\psi(\cdot) = \pi_R^\psi f^\psi$ then $\psi \varphi(\cdot) = \pi f(\cdot)$, where $\pi = \pi_R^\psi f^\psi \pi_Q^\varphi (f^\varphi)^{-1} \in \mathfrak{S}_R$, and $f = f^\psi f^\varphi \in F_{k,1}$.

Questions left open: What are all the torsion subgroups of $G_{k,1}$? What are all the torsion, non-torsion, or torsion-free subgroups S of $G_{k,1}$ for which there is a unique factorization $G_{k,1} = S \cdot F_{k,1}$? Are the groups $\bigcup_{n \geq 0} \mathfrak{S}_{P_1 A^n}$ and $\bigcup_{n \geq 0} \mathfrak{S}_{P_2 A^n}$ non-isomorphic if they do not obey the conditions of Theorem 4.5?

5 Generators of lpV and reversible computing

We are interested in the computation of elements of V and of lpV by circuits. For general information on circuits see [29, 28]; good references on reversible circuits are [12, 26, 27, 23]. We will use the following fundamental results from the field of *reversible computing*:

- (V. Shende, A. Prasad, I. Markov, J. Hayes [23]) Every *even* permutation of the set $\{0, 1\}^n$ can be computed by a circuit constructed only from bijective gates of type NOT, C-NOT, CC-NOT.

The gates NOT, C-NOT, CC-NOT are well known in the field of reversible computing, and are defined as follows:

NOT: $x \in \{0, 1\} \mapsto \bar{x} \in \{0, 1\}$ is the usual negation operation;

C-NOT: $(x, y) \in \{0, 1\}^2 \mapsto (x, y \oplus x) \in \{0, 1\}^2$ is the *controlled* NOT, also called the “Feynman gate”;

CC-NOT: $(x, y, z) \in \{0, 1\}^3 \mapsto (x, y, z \oplus (x \& y)) \in \{0, 1\}^3$ is the *doubly controlled* NOT, with $\oplus$ denoting the usual exclusive OR (i.e., addition modulo 2), and $\&$ denoting the logical AND (i.e., multiplication modulo 2). The doubly controlled NOT is usually called the “Toffoli gate” [12, 26, 27].

- [23] For any positive integer n and any permutation $\pi \in \mathfrak{S}_{2^n}$, the permutation

$$(x_1, \dots, x_n, x_{n+1}) \in \{0, 1\}^{n+1} \mapsto \pi(x_1, \dots, x_n) \cdot x_{n+1} \in \{0, 1\}^{n+1}$$

is *even*. Here, “.” denotes concatenation. Indeed, one transposition $(u|v)$ (with $u, v \in \{0, 1\}^n$) is now replaced by $(u0|v0)(u1|v1)$ (i.e., two transpositions).

As a consequence, every odd permutation of $\{0, 1\}^n$ can be computed by a circuit that only makes use of bijective gates of type NOT, C-NOT, CC-NOT, and that uses an extra identity wire $x_{n+1} \mapsto x_{n+1}$.

- (T. Toffoli [26, 27]) An odd permutation of $\{0, 1\}^n$ cannot be computed by any circuit containing only bijective gates with fewer than n input-output wires. Hence for odd permutations, the extra identity wire is necessary for bijective computing with a finite collection of gate types.

The above results have some interesting consequences for the group lpV :

First, the overall restriction operation for elements of the Thompson group V (which replaces each $\varphi(x) = y$ by the pair $\varphi(x0) = y0, \varphi(x1) = y1$ for all x in the domain of φ) now receives a very concrete interpretation for elements of lpV : For an element φ of lpV , the overall restriction is equivalent to

adding an *identity wire* at the “bottom” of the circuit (i.e., at the right-most position for boolean variables).

Second, another consequence of the above concerns the generators of lpV . Let N, C, T be the partial maps $\{0, 1\}^* \rightarrow \{0, 1\}^*$ defined as follows, where $w \in \{0, 1\}^*$ is any bitstring; $N : x_1 w \mapsto \bar{x}_1 w$, $C : x_1 x_2 w \mapsto x_1 (x_2 \oplus x_1) w$, and $T : x_1 x_2 x_3 w \mapsto x_1 x_2 (x_3 \oplus (x_2 \& x_1)) w$. These maps are just the NOT, C-NOT, CC-NOT gates, *applied only to the first (left-most) bits* of a binary string. We leave N, C, T undefined on bit strings that are too short.

Note that the engineering convention consists of using the same name (e.g., “not”, “c-not”, etc.) for the same operation on different variables in an sequence of variables. But this convention would not be correct in our setting; e.g., negating the first bit in a string is different from negating the second bit. In order to implement the operations N, C, T on all bit-positions, i.e., in order to obtain the gate types NOT, C-NOT, CC-NOT in the engineering sense of the word, we also introduce the position transpositions $\tau_{i,j} : \{0, 1\}^* \rightarrow \{0, 1\}^*$ (where $1 \leq i < j$), defined by

$$\tau_{i,j} : u x_i v x_j w \mapsto u x_j v x_i w,$$

where $u, v, w \in \{0, 1\}^*$, $|u| = i - 1$, $|v| = j - 1 - i$; and we leave $\tau_{i,j}(s)$ undefined when $|s| < j$. Note that $\tau_{i,j}$ does not transpose a pair of words $\in \{0, 1\}^*$, but boolean variables (or positions within words).

Proposition 5.1 *The group lpV is generated by the set $\{N, C, T\} \cup \{\tau_{i,i+1} : 1 \leq i\}$. More generally, $lpG_{k,1}$ is generated by $\Gamma_k \cup \{\tau_{i,i+1} : 1 \leq i\}$ for some finite set Γ_k .*

The finite alternating group $\mathfrak{A}_{2^n}$ (acting on $\{0, 1\}^n$) is generated by the set $\{N, C, T\} \cup \{\tau_{i,i+1} : 1 \leq i < n\}$.

Proof. The Proposition is immediate from the above observations, and in particular the work [23].
□

Application: An intuitive generating set for V

The $lpV \cdot F$ factorization, together with the nice generating set given above for lpV enables us to find a finite generating set for V with a nice “physical” interpretation. It follows from the $lpV \cdot F$ factorization that $\{N, C, T\} \cup \{\tau_{i,i+1} : 1 \leq i\} \cup \{\sigma, \sigma_1\}$ is a generating set of V , where $\{\sigma, \sigma_1\}$ is the generating set of F given in [9] with tables

$$\sigma = \begin{bmatrix} 00 & 01 & 1 \\ 0 & 10 & 11 \end{bmatrix}, \quad \sigma_1 = \begin{bmatrix} 0 & 100 & 101 & 11 \\ 0 & 10 & 110 & 111 \end{bmatrix}.$$

We will see that σ_1 is a “controlled lowering” of σ (defined below). In [2] we saw that σ can be viewed as the $\mathbb{Z}$ -shift $0^n 1 \mapsto 0^{n-1} 1$, $01 \mapsto 10$, $1^n 0 \mapsto 1^{n+1} 0$, on the maximal prefix code $0^* 01 \cup 1^* 10$.

Since V is finitely generated, only a finite subset of $\{\tau_{i,i+1} : 1 \leq i\}$ will be needed for generating V . Surprisingly, it turns out that in the presence of the other generators, the Toffoli gate T will not be needed for V . In detail we have:

Proposition 5.2 *The Thompson group V is generated by the finite set $\{N, C, \tau_{1,2}, \sigma, \sigma_1\}$, where N is the NOT gate applied to the first wire, C is C-NOT (controlled NOT, a.k.a. Feynman gate) applied to the first two wires, $\tau_{1,2}$ is the transposition of the first two wires, and σ, σ_1 generate the Thompson group F .*

Proof. We start out with the Higman generators $\kappa, \lambda, \mu, \nu$ of V (see [16]), whose tables are

$$\kappa = \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}, \quad \lambda = \begin{bmatrix} 00 & 01 & 1 \\ 00 & 1 & 01 \end{bmatrix}, \quad \mu = \begin{bmatrix} 0 & 10 & 11 \\ 10 & 0 & 11 \end{bmatrix}, \quad \nu = \begin{bmatrix} 00 & 01 & 10 & 11 \\ 00 & 10 & 01 & 11 \end{bmatrix}.$$

We see that $\kappa = N$ and $\nu = \tau_{1,2}$. For λ and μ we apply the $lpV \cdot F$ factorization algorithm, which leads to

$$\lambda(\cdot) = \begin{bmatrix} 00 & 01 & 10 & 11 \\ 00 & 10 & 11 & 01 \end{bmatrix} \cdot \begin{bmatrix} 00 & 010 & 011 & 1 \\ 00 & 01 & 10 & 11 \end{bmatrix}(\cdot)$$

The right factor belongs to F , hence it is generated by $\{\sigma, \sigma_1\}$. It is easy to check that the first factor is equal to $\tau_{1,2} \cdot C(\cdot)$; recall that C has the table $\begin{bmatrix} 00 & 01 & 10 & 11 \\ 00 & 01 & 11 & 10 \end{bmatrix} = \begin{bmatrix} 0 & 10 & 11 \\ 0 & 11 & 10 \end{bmatrix}$.

A similar calculation leads to a factorization $\mu(\cdot) = \tau_{1,2} \cdot C \cdot \tau_{1,2} \cdot N \cdot \tau_{1,2} \cdot f(\cdot)$, for some $f \in F$. $\square$

The lowering operation

The following operation, inspired by circuits, gives further insight into lpV and F . For any integer $d > 0$ we define

$$\begin{aligned} \varphi \in G_{k,1} &\longmapsto (\varphi)_d \in G_{k,1} \text{ by} \\ (\varphi)_d(zx) &= z \varphi(x) \text{ for all } z \in A^d, x \in \text{Dom}(\varphi). \end{aligned}$$

Recall that A^d is the set of all words of length d over A . It is easy to see that for each $d > 0$, the operation $\varphi \rightarrow (\varphi)_d$ is an *endomorphism* of $G_{k,1}$, which is injective but not surjective; it is also an endomorphism of $lpG_{k,1}$, of $F_{k,1}$, of $T_{k,1}$, and of $lpT_{k,1}$.

The circuit interpretation of the operation $\varphi \rightarrow (\varphi)_d$ is that the “gate” φ is lowered by d positions in the circuit through the introduction of d identity wires on top of the “gate” φ (i.e., at the left end of the list of input variables). While φ is applied to the boolean variables $x_1, x_2, \dots$, the lowered gate will be applied to the variables $x_{d+1}, x_{d+2}, \dots$. This is commonly done in circuits, as it allows the designer to place gates at any place in the circuit. In electrical engineering, traditionally no distinction is made between a gate; e.g., the C-NOT operation and its lowerings are all just called “C-NOT gates”. The lowering operation is an important link between circuits and their representation by groups or monoids of functions.

The lowering operation can be expressed in terms of the transpositions $\tau_{i,i+1}$, although the formula depends on the length ℓ of the longest word $\in A^*$ appearing in the table of φ . We have: $(\varphi)_d(\cdot) = \pi^{-1} \varphi \pi(\cdot)$, where π is the following permutation of bit positions:

$$\begin{aligned} \text{If } d+1 > \ell \text{ then } \pi(\cdot) &= \begin{pmatrix} 1 & 2 & \dots & \ell & d+1 & d+2 & \dots & d+\ell \\ d+1 & d+2 & \dots & d+\ell & 1 & 2 & \dots & \ell \end{pmatrix}. \\ \text{If } d+1 \leq \ell \text{ then } \pi(\cdot) &= \begin{pmatrix} 1 & 2 & \dots & d & d+1 & d+2 & \dots & d+\ell \\ 1+\ell & 2+\ell & \dots & d+\ell & 1 & 2 & \dots & \ell \end{pmatrix}. \end{aligned}$$

When we write elements of $G_{k,1}$ as elements of the Cuntz algebra $\mathcal{O}_k$ (according to [2] and [21]), we see that the lowering operation is an endomorphism of $\mathcal{O}_k$ given by the formula

$$\gamma \in \mathcal{O}_k \longmapsto (\gamma)_d = \sum_{z \in A^d} z \gamma \bar{z} \in \mathcal{O}_k.$$

Note that all transpositions of variables (or wires) $\tau_{i,i+1}$ are obtained from the transposition of variables $\tau_{1,2}$ by $\tau_{i,i+1} = (\tau_{1,2})_{i-1}$. So, the lowering operations, together with a finite set of elements of $lpG_{k,1}$, yields a generating set of $lpG_{k,1}$. For $G_{k,1}$ we already saw that the transpositions of variables are redundant as generators (since $G_{k,1}$ is finitely generated), but that the use of the transpositions of variables shortens the word length; we will see (Theorem 7.5) that when the transpositions of variables are added to a finite generating set of $G_{k,1}$ then the word length becomes approximately the same as the bijective-circuit complexity. For $F_{k,1}$ it will be interesting to consider generating sets of the form $\Gamma \cup \bigcup_{d \geq 1} (\Gamma)_d$, where Γ is any finite generating set of $F_{k,1}$, and where $(\Gamma)_d = \{(f)_d : f \in \Gamma\}$ (see the open problems at the end of Section 6).

We can define the **controlled lowering operation**; we fix any string $c \in A^*$, called the “control string” and define

$$\begin{aligned} \varphi \in G_{k,1} &\longmapsto (\varphi)_c \in G_{k,1} \text{ by} \\ (\varphi)_c(cx) &= c \varphi(x) \text{ for all } x \in \text{Dom}(\varphi), \text{ and} \\ (\varphi)_c(p\alpha) &= p\alpha \text{ where } p <_{\text{pref}} c, \alpha \in A, p\alpha \not\leq_{\text{pref}} c; \end{aligned}$$

so here p is any strict prefix of c (i.e., $p \neq c$), and $\alpha \in A$ is such that $p\alpha$ is *not* a prefix of c . So, $\text{domC}((\varphi)_c) = c \cdot \text{domC}(\varphi) \cup \{p\alpha : p <_{\text{pref}} c, \alpha \in A, p\alpha \not\leq_{\text{pref}} c\}$, and $\text{imC}((\varphi)_c) = c \cdot \text{imC}(\varphi) \cup \{p\alpha : p <_{\text{pref}} c, \alpha \in A, p\alpha \not\leq_{\text{pref}} c\}$.

It is easy to see that for each $c \in A^*$, the operation $\varphi \rightarrow (\varphi)_c$ is an *endomorphism* of $G_{k,1}$, which is injective but not surjective; it is also an endomorphism of $lpG_{k,1}$, of $F_{k,1}$, of $T_{k,1}$, and of $lpT_{k,1}$. In Cuntz algebra notation, the operation takes the form

$$\gamma \in \mathcal{O}_k \longmapsto (\gamma)_c = c\gamma\bar{c} + \sum_{p,\alpha} p\alpha\bar{p}\bar{\alpha} \in \mathcal{O}_k.$$

where p ranges over the strict prefixes of c and α ranges over the letters of A such that $p\alpha$ is not a prefix of c . In $\mathcal{O}_k$ the controlled lowering operation is a multiplicative endomorphism, but it is not additive.

Observe that for the generators $\{\sigma, \sigma_1\}$ of F seen before, the second generator is the controlled lowering of the first with control string 1; this explains our notation for σ_1 .

6 Generalized word problem, distortion of $F_{k,1}$ and $lpG_{k,1}$ in $G_{k,1}$

Proposition 6.1 *Over any finite generating set of $G_{k,1}$ the generalized word problem of $F_{k,1}$ in $G_{k,1}$ can be decided in cubic deterministic time.*

Similarly, over any finite generating set of $G_{k,1}$ the generalized word problem of $lpG_{k,1}$ in $G_{k,1}$, and more generally, the generalized word problem of $\bigcup_m \mathfrak{S}_{PA^m}$ in $G_{k,1}$ (for any finite maximal prefix code P) can be decided in cubic deterministic time.

Proof. By Proposition 4.2 of [2], if φ is given by a word of length n over a finite generating set of $G_{k,1}$ then a table for φ (not necessarily maximally extended) can be computed in time $O(n^3)$. By Proposition 3.5 of [2], the length n provides a linear upper bound on the size of this table. Also, every table entry has length $\leq cn$. More precisely, the table has the form $((x_1, y_1), \dots, (x_N, y_N))$, where $|x_i|, |y_i|, N \leq cn$ (for some constant $c \geq 1$). The sets $\{x_1, \dots, x_N\}$ and $\{y_1, \dots, y_N\}$ are maximal prefix codes, and $\varphi(x_i) = y_i$ for $i = 1, \dots, N$.

To check whether φ belongs to $F_{k,1}$ we first sort the table according to the input entries, with respect to dictionary order; more precisely, we sort the pairs of the table $((x_1, y_1), \dots, (x_N, y_N))$ according the x -coordinates, in time $\leq O(n^2 \log n)$; indeed, there are $O(n \log n)$ sorting steps, and since each word has length $\leq cn$, each word comparison takes time $O(n)$. Then we check whether the resulting x -sorted table is now also in sorted form regarding the y -coordinates; this takes quadratic time, as there are $O(n)$ words of length $O(n)$.

To check whether φ belongs to $lpG_{k,1}$ we check, in time $\leq O(n^2)$, that $|x_i| = |y_i|$ for $i = 1, \dots, N$. And to check whether φ belongs to $\bigcup_m \mathfrak{S}_{PA^m}$ we note first that P is a fixed finite maximal prefix code, independent of φ . We restrict φ so that every table entry receives length $\geq \max\{|p| : p \in P\}$. This multiplies the table size of φ by a constant, at most (since P and $\max\{|p| : p \in P\}$ are fixed). So we can assume that each x_i and y_i in the table of φ has a prefix in P . Now for x_1 , find the prefix $p_1 \in P$ of x_1 , so $x_1 = p_1 s_1$ for some $s_1 \in A^*$, and let $m_0 = |s_1|$. Thus, φ belongs to $\bigcup_m \mathfrak{S}_{PA^m}$ iff $\varphi \in \mathfrak{S}_{PA^{m_0}}$. So, we now write each x_i and each y_i in the form ps with $p \in P$ and check that $|s| = m_0$; this holds (for all s obtained) iff $\varphi \in \mathfrak{S}_{PA^{m_0}}$. Checking this takes time $\leq O(n^2)$. $\square$

Since $lpG_{k,1} \cap F_{k,1} = \{1\}$, we have the following equivalence: $w = 1$ (as elements of $G_{k,1}$) iff $w \in lpG_{k,1}$ and $w \in F_{k,1}$. Thus, the word problem of $G_{k,1}$ reduces (by a one-to-one linear-time reduction) to the conjunction of the generalized word problem of $lpG_{k,1}$ in $G_{k,1}$ and the generalized word problem of $F_{k,1}$ in $G_{k,1}$. (Here, the reduction function is just the identity map.) The same is true with $lpG_{k,1}$ replaced by $\bigcup_m \mathfrak{S}_{PA^m}$ (for any chosen finite maximal prefix code P).

Hence, the deterministic (or nondeterministic, or co-nondeterministic) time complexity of the word problem of $G_{k,1}$ is a lower bound for the deterministic (respectively nondeterministic, or co-nondeterministic) time complexity of the generalized word problem of $\bigcup_n \mathfrak{S}_{PA^m}$ in $G_{k,1}$ or the generalized word problem of $F_{k,1}$ in $G_{k,1}$, or both. More formally, we have the following:

Definition 6.2 *We say that a language (or decision problem) L is as hard as coNP iff there is a coNP-complete problem L_0 such that for every function $t(\cdot)$ that is a deterministic time complexity lower bound for infinitely many instances of L_0 we have: Some function $\geq c \cdot t(\cdot)$ is a deterministic time complexity lower bound for infinitely many instances of L (for some constant $c > 0$).*

Definition 6.3 *Let G be a group with generating set A . Suppose every generator $\alpha \in A$ has been assigned a “length” $|\alpha| \in \mathbb{N}$. Typically, if A is finite then $|\alpha| = 1$ for all $\alpha \in A$. For the position transpositions $\tau_{i,j}$ ($1 \leq i < j$) we take $|\tau_{i,j}| = j$.*

The length of a word $w = a_1 \dots a_n$ over A is defined by $|w| = \sum_{j=1}^n |a_j|$.

The word length $|g|_A$ of $g \in G$ over A is defined to be the shortest length of any word (over A) that represents g .

For a group with generating set A we often say “a word over A ” when we actually mean “a word over $A \cup A^{-1}$ ”; we will also use the notation $A^{\pm 1}$ for $A \cup A^{-1}$.

Proposition 6.4 *Let $\Gamma_{k,1}$ be a finite generating set of $G_{k,1}$ but suppose that elements of $G_{k,1}$ are given over the infinite generating set $\Gamma_{k,1} \cup \{\tau_{i,j} : 1 \leq i < j\}$. Then the generalized word problem, in $G_{k,1}$, of either $F_{k,1}$ or $lpG_{k,1}$, or both, is as hard as coNP.*

Similarly, if $P \in A^*$ is a finite maximal prefix code then the generalized word problem, in $G_{k,1}$, of either $F_{k,1}$ or $\bigcup_n \mathfrak{S}_{PA^m}$, or both, is as hard as coNP. Moreover, these problems are in coNP.

Proof. The word problem of $G_{k,1}$ over the generating set $\Gamma_{k,1} \cup \{\tau_{i,j} : 1 \leq i < j\}$ is coNP-complete [3]. The hardness then follows from the above conjunctive reduction. $\square$

Definition 6.5 *Let G_1 be a group with generating set A_1 , and let G_2 be a subgroup of G_1 with generating set A_2 . A function $f : \mathbb{N} \rightarrow \mathbb{N}$ is called a **distortion** function for G_2 within G_1 , with respect to the generators A_1 , respectively A_2 , iff for all $g_2 \in G_2$: $|g_2|_{A_2} \leq f(|g_2|_{A_1})$.*

The distortion function of G_2 within G_1 , with respect to the generators A_1 , respectively A_2 , is the smallest distortion function.

Proposition 6.6 *If we use finite generating sets for both $G_{k,1}$ and $F_{k,1}$ then $F_{k,1}$ has linear distortion in $G_{k,1}$.*

Proof. For any element $g \in G_{k,1}$ we have $\|g\| \leq c_1 |g|_G$, by Proposition 3.5 of [2]; here, $\|g\|$ is the table size of the element g , c_1 is a positive constant, and $|g|_G$ is the word length of g over some chosen, fixed finite generating set of $G_{k,1}$. By Theorem 2.5 of [9], $|g|_F \leq c_2 \|g\|$, where c_2 is a positive constant, and $|g|_F$ is the word length of g over some chosen, fixed finite generating set of $F_{k,1}$. Hence, $|g|_F \leq c_1 c_2 |g|_G$, so the distortion of $F_{k,1}$ in $G_{k,1}$ is linear. $\square$

Problems left open:

1. Over the generating set $\Gamma_{k,1} \cup \{\tau_{i,j} : 1 \leq i < j\}$ of $G_{k,1}$, are the generalized word problems of the subgroups $F_{k,1}$, $lpG_{k,1}$, and $\bigcup_n \mathfrak{S}_{PA^n}$ each coNP-complete?
2. We saw that lpV is generated by $\{N, C, T\} \cup \{\tau_{i,i+1} : 1 \leq i\}$. What is the *distortion* of lpV (over this generating set) within the Thompson group V (with V over the generating set $\Gamma_V \cup \{\tau_{i,i+1} : 1 \leq i\}$, where Γ_V is any finite generating set of V)? We will see in the next Section that this distortion has a close connection to the relation between different kinds of bijective circuits.
3. We saw that F is generated by a two-element set $\{\sigma, \sigma_1\}$, and hence also by $\{(\sigma)_d, (\sigma_1)_d : d > 0\}$. What is the *distortion* of F within V , when F is taken over the generating set $\{(\sigma)_d, (\sigma_1)_d : d > 0\}$, and V is taken over the generating set $\Gamma_V \cup \{\tau_{i,i+1} : 1 \leq i\}$?

7 Complexity of F and of the factorization of V

We saw that in the factorization $\varphi = \pi f$ with $\pi \in lpV$ and $f \in F$, the table sizes of π and of f can be exponentially larger than the table size of φ . We will now investigate the circuit complexity of π and f , compared to that of φ . We will also show that if $f \in F$ then the circuit complexity of f^{-1} is not much higher than the circuit complexity of f ; in other words, the elements of the Thompson group F do not have much computational asymmetry (and in particular, they cannot be one-way functions). And we will show that some problems in V are coNP-complete or $\#\mathcal{P}$ -complete; in particular, the problem of finding the $lpV \cdot F$ factorization is $\#\mathcal{P}$ -complete. In this section we focus on the Thompson groups V and F , but the results could easily be extended to $G_{k,1}$ and $F_{k,1}$.

7.1 Circuit complexity and Thompson groups

Since an element $\varphi \in V$ is a partial function mapping bitstrings to bitstrings, it is natural to view φ as a boolean function, to be computed by a boolean circuit. However, unless $\varphi \in lpV$, the inputs and the outputs of φ do not have a fixed length. So the traditional concept of a combinational boolean circuit cannot be applied directly to elements of V .

Let $\varphi : P \rightarrow Q$ be a bijection between finite maximal prefix codes $P, Q \subset \{0, 1\}^*$, representing an element of V . We will use ternary logic over the alphabet $\{0, 1, \perp\}$, where $\perp$ is a new letter used for padding bitstrings. Let m be the length of the longest bitstring in P , and let n be the length of the longest bitstring in Q . We define $\varphi^\perp : \{0, 1, \perp\}^m \rightarrow \{0, 1, \perp\}^n$ as follows:

$$\text{For } p \in P, \quad \varphi^\perp(p \perp^{m-|p|}) = \varphi(p) \perp^{n-|\varphi(p)|}.$$

$$\text{For } x \in \{0, 1, \perp\}^m - \{p \perp^{m-|p|} : p \in P\} \text{ we let } \varphi^\perp(x) = \perp^n.$$

We will use the notation

$$P^\perp = \{p \perp^{m-|p|} : p \in P\} = P \perp^* \cap \{0, 1, \perp\}^m, \text{ where } m = \max\{|p| : p \in P\};$$

$$Q^\perp = \{q \perp^{n-|q|} : q \in Q\} = Q \perp^* \cap \{0, 1, \perp\}^n, \text{ where } n = \max\{|q| : q \in Q\}.$$

We call $P^\perp$, $Q^\perp$, and $\varphi^\perp$ the **padding** of P , Q , respectively φ . Note: For $\varphi \in V = G_{2,1}$, the padding $\varphi^\perp$ is *not* to be viewed as an element of $lpG_{3,1}$.

We observe that for the restrictions to $P^\perp$ or to $Q^\perp$ we have $(\varphi^\perp|_{P^\perp})^{-1} = (\varphi^{-1})^\perp|_{Q^\perp}$; the restriction $\varphi^\perp|_{P^\perp}$ is bijective (but $\varphi^\perp$ is not bijective in general). When $\text{im}C(\varphi) = \text{dom}C(\psi)$ we also have $(\psi\varphi)^\perp = \psi^\perp\varphi^\perp$.

To compute the function $\varphi^\perp : \{0, 1, \perp\}^m \rightarrow \{0, 1, \perp\}^n$ we consider ternary-logic combinational circuits with gates over the alphabet $\{0, 1, \perp\}$. We assume that a finite, computationally universal set of ternary logic gates has been chosen; we ignore the details since they only affect the circuit complexity by a constant multiple. We also use the (unbounded) set of wire-swap operations $\tau_{i,i+1}$.

For such a circuit, the **size of the circuit** is defined to be the number of gates together with the number of wires (links between gates or between gates and inputs or outputs). Note that a “lowered gate” $(\gamma)_d$ (i.e., the gate γ applied to the wires $d+1, d+2$, etc., as defined at the end of Section 5) is counted as one gate (independently of d). Also, in a circuit each wire-crossing $\tau_{i,i+1}$ will be counted as one gate (independently of i). Note that here we are talking about circuit size, not about word length.

Remarks:

- (1) The idea of padding with $\perp$ works for the Thompson-Higman group $G_{k,1}$ in general, by using $(A \cup \{\perp\})$ -valued logic. The gates that we use include the wire-crossings $\tau_{i,i+1}$.
- (2) In [1] we will follow another, more algebraic, approach for defining circuit complexity of elements of V . We embed V into a certain finitely generated partial transformation *monoid* M acting on $\{0, 1, \perp\}^*$, and we take the word-length of φ in M as the circuit complexity of φ . We will prove in [1] that there are monoids M that, over certain generators, can “simulate” logic gates, and that in such monoids word-length is closely related to circuit complexity.

Since the functions $\varphi : P \rightarrow Q$ considered here are elements of V , hence bijective, it is natural to also introduce **bijective $\{0, 1, \perp\}$ -valued circuits**. A $\{0, 1, \perp\}$ -valued circuit is said to be bijective iff the gates that make up the circuit are the wire-swap operations $\tau_{i,i+1}$ ($i \geq 1$), and a set of gates derived from the elements of some fixed finite generating set Γ_V of V . The latter means, more precisely, that the gates derived from Γ_V are of the form $((\gamma)_d)^\perp$ where each γ is a restriction of an element of Γ_V . Recall that $(\gamma)_d$ (for $d \geq 0$) is the lowering of γ (defined at the end of Section 5).

In this paper, unless we specifically mention “bijective” or “ $\{0, 1, \perp\}$ -valued”, the word “circuit” will refer to a general boolean circuit (not necessarily bijective).

Comparison between $\{0, 1, \perp\}$ -valued circuits and boolean (i.e., $\{0, 1\}$ -valued) circuits:

In the general (not necessarily bijective) case, a $\{0, 1, \perp\}$ -valued circuit can be simulated by a traditional binary-logic circuit (e.g., by encoding the ternary values $0, 1, \perp$ by the binary strings $00, 11, 01$ respectively, with 10 also serving as a code for $\perp$). Thus, there is no essential difference between general $\{0, 1, \perp\}$ -valued circuits and general boolean circuits.

However, bijective $\{0, 1, \perp\}$ -valued circuits have greater generality than bijective boolean circuits. First, bijective boolean circuits have input-output functions belonging to lpV only; on the other hand, input-output functions of bijective $\{0, 1, \perp\}$ -valued circuits are the paddings of all the elements of V . Also, the input-output function of a bijective $\{0, 1, \perp\}$ -valued circuit is only bijective as a function $P^\perp \rightarrow Q^\perp$, not as a function $\{0, 1, \perp\}^m \rightarrow \{0, 1, \perp\}^n$, whereas the input-output function of a bijective boolean circuit is a permutation of $\{0, 1\}^m$ for some m .

Moreover, even for $\varphi \in lpV$ the smallest size of a bijective $\{0, 1, \perp\}$ -valued circuit computing φ is the word length of φ over the generators of V (as we shall show in Theorem 7.5 below), whereas the smallest size of a bijective boolean circuit computing φ is the word length of φ over the generators of lpV . Thus, we will see that the relation between the two bijective circuit sizes is approximately the *distortion* of lpV within V . Here the generating set of V is $\Gamma_V \cup \{\tau_{i,i+1} : 1 \leq i\}$ for any finite generating set Γ_V of V , and lpV is generated by $\{N, C, T\} \cup \{\tau_{i,i+1} : 1 \leq i\}$ as seen before. Finding the distortion of lpV within V is one of our open problems mentioned at the end of Section 6. Theorem 7.5 below will give a precise connection between the two kinds of bijective circuit sizes, word lengths in V or in lpV , and the distortion of lpV in V .

Definition 7.1 *Let $\Gamma_{k,1}$ be a finite generating set of $G_{k,1}$, and let w be a word over the generating set $\Gamma_{k,1} \cup \{\tau_{i,i+1} : 1 \leq i\}$ of $G_{k,1}$. The **length** of $w = a_1 \dots a_n$ is $|w| = \sum_{j=1}^n |a_j|$, where $|a_j| = 1$ if $a_j \in \Gamma_{k,1}$ and $|a_j| = i+1$ if $a_j = \tau_{i,i+1}$.*

For $\varphi \in G_{k,1}$, the **word length** of φ over $\Gamma_{k,1} \cup \{\tau_{i,i+1} : 1 \leq i\}$ is the shortest length of any word (over the above generators) that represents φ .

Observe that $\tau_{i,i+1}$ is counted differently for circuit size than for word length ($\tau_{i,i+1}$ is counted as 1 in circuit size but as $i + 1$ in the word length).

The following definition compares bijective padded circuits for elements of lpV with boolean bijective circuits. Note that in this definition we only consider circuits for computing elements of lpV .

Definition 7.2 An unpadding cost function from bijective $\{0, 1, \perp\}$ -valued circuits to bijective binary circuits is any function $U : \mathbb{N} \rightarrow \mathbb{N}$ such that the following holds: For all $\varphi \in lpV$ and any bijective $\{0, 1, \perp\}$ -valued circuit of size m for φ there exists a bijective binary circuit of size $\leq U(m)$ for φ .

The unpadding cost function $u(\cdot)$ is the minimum unpadding cost function.

Definition 7.3 Two functions $f_1, f_2 : \mathbb{N} \rightarrow \mathbb{N}$ are said to be **linearly related** iff there are constants c_0, c_1, c_2 , all ≥ 1 , such that for all $n \geq c_0$: $f_1(n) \leq c_1 f_2(c_1 n)$ and $f_2(n) \leq c_2 f_1(c_2 n)$.

The functions f_1, f_2 are said to be **polynomially related** iff there are constants c_0, c_1, c_2 , all ≥ 1 , such that for all $n \geq c_0$: $f_1(n) \leq c_1 f_2(c_1 n^{c_1})^{c_1}$ and $f_2(n) \leq c_2 f_1(c_2 n^{c_2})^{c_2}$.

The following theorem motivates $\{0, 1, \perp\}$ -valued circuits, as well as the concept of word length over the generating set $\Gamma_V \cup \{\tau_{i,i+1} : 1 \leq i\}$ for V . It again motivates our use of the infinite set $\{\tau_{i,i+1} : 1 \leq i\}$ for generating V , inspite of the fact that V is finitely generated. It also reinforces the connection between Thompson groups and bijective (“reversible”) computing, seen before. In [1] we will generalize Theorem 7.5 to a connection between general circuit size and the word size in the “Thompson monoids” (the latter being a generalization of the Thompson-Higman groups to monoids). We will only state the Theorem for V and for binary or $\{0, 1, \perp\}$ -valued circuit, although it could easily be generalized to $G_{k,1}$. First a lemma:

Lemma 7.4 Let $a_n, \dots, a_1 \in V$ be given by table and let ℓ be the length of the longest words in the tables of $a_n, \dots, a_1$. Then $a_n, \dots, a_1$ have restrictions $\alpha_n, \dots, \alpha_1$, respectively, such that

- $\text{domC}(\alpha_{j+1}) = \text{imC}(\alpha_j)$ for $n > j \geq 1$, and
- all words in the tables of α_j ($n \geq j \geq 1$) have lengths $\leq n\ell$.

Proof. For $\varphi \in V$ we will describe the table of φ as a set of input-output pairs, of the form $\{(u_i, v_i) : i = 1, \dots, I\}$. We also use tables to represent elements of V in non-maximally extended form; we will mention explicitly when we assume maximal extension.

Claim. Let $a_i \in V$ (for $i = 1, \dots, n$) be given by tables $\{(x_j^{(i)}, y_j^{(i)}) : j = 1, \dots, r\}$, not necessarily in reduced form. Thus $\text{domC}(a_i) = \{x_j^{(i)} : j = 1, \dots, r\}$, and $\text{imC}(a_i) = \{y_j^{(i)} : j = 1, \dots, r\}$. We assume that $\text{domC}(a_{i+1}) = \text{imC}(a_i)$ for $i = 1, \dots, n-1$. Let ℓ be an upper bound on the length of all the words in $\bigcup_{i=1}^n \text{domC}(a_i) \cup \text{imC}(a_i)$. For $j = 1, \dots, r$, let $S_j = \{s_{j,k} : 1 \leq k \leq |S_j|\}$ be a finite maximal prefix code over $\{0, 1\}$.

Then α_i (for $i = 1, \dots, n$), defined by the table $\{(x_j^{(i)} s_{j,k}, y_j^{(i)} s_{j,k}) : 1 \leq j \leq r, 1 \leq k \leq |S_j|\}$, is a restriction of a_i satisfying:

- $\text{domC}(\alpha_{i+1}) = \text{imC}(\alpha_i)$ for $n > i \geq 1$, and
- all words in the tables of α_i ($n \geq i \geq 1$) have lengths $\leq \max\{|s_i| : 1 \leq i \leq r\} + \ell$.

Proof of the Claim: Since $\{x_j^{(i+1)} : j = 1, \dots, r\} = \text{domC}(a_{i+1}) = \text{imC}(a_i) = \{y_j^{(i)} : j = 1, \dots, r\}$, it follows immediately that $\{x_j^{(i+1)} s_{j,k} : 1 \leq j \leq r, 1 \leq k \leq |S_j|\} = \{y_j^{(i)} s_{j,k} : 1 \leq j \leq r, 1 \leq k \leq |S_j|\}$. Hence $\text{domC}(\alpha_{i+1}) = \text{imC}(\alpha_i)$.

Also, $|x_j^{(i)} s_{j,k}| \leq \ell + \max\{|s_i| : 1 \leq i \leq r\}$ (and similarly for $|y_j^{(i)} s_{j,k}|$), hence we have the claimed length bound. This proves the Claim.

Let us now prove Lemma 7.4 by induction on n . The Lemma is obvious when $n = 1$. Given $a_i \in V$ (for $i = n, \dots, 1$, with $n \geq 2$), we use the Lemma by induction for $a_{n-1}, \dots, a_1$. So we can assume that $\text{domC}(a_{i+1}) = \text{imC}(a_i)$ for $n-1 > i \geq 1$, and all words in the tables of a_i ($n-1 \geq i \geq 1$) have lengths $\leq (n-1)\ell$. Let us denote $\text{domC}(a_{i+1}) = \text{imC}(a_i)$ by P_i ; so we have $P_0 \xrightarrow{a_1} P_1 \xrightarrow{a_2} \dots \xrightarrow{a_{n-2}} P_{n-2} \xrightarrow{a_{n-1}} P_{n-1}$.

We consider the product $a_n \cdot (a_{n-1} \dots a_1)$. We will find a restriction α_n of a_n , and a restriction $\overline{a_{n-1} \dots a_1}$ of $a_{n-1} \dots a_1$, such that $\text{domC}(\alpha_n) = \text{imC}(\overline{a_{n-1} \dots a_1})$. We also want to restrict $a_{n-1}, \dots, a_1$ to functions $\alpha_{n-1}, \dots, \alpha_1$ such that $\text{domC}(\alpha_{i+1}) = \text{imC}(\alpha_i)$ for $n-1 > i \geq 1$. Two cases arise:

Case 1: Every word in P_{n-1} has length $\geq \ell$.

By the assumptions of Lemma 7.4, every word in the table of a_n has length $\leq \ell$. Therefore, all we need to do to obtain α_n and $\alpha_{n-1}, \dots, \alpha_1$ is to restrict a_n so that $\text{domC}(\alpha_n)$ becomes P_{n-1} . No restriction of $a_{n-1} \dots a_1$ is needed, i.e., $\alpha_i = a_i$ for $i = n-1, \dots, 1$, and $\overline{a_{n-1} \dots a_1} = a_{n-1} \dots a_1$. Hence the longest word in $P_0, P_1, \dots, P_{n-1}$ has length $\leq (n-1)\ell$.

The longest word in the table of α_n has length $\leq \max\{|p| : p \in P_{n-1}\} + \ell$, by the Claim (applied to α_n and $a_{n-1} \dots a_1$). Hence the longest word in the table of α_n has length $\leq (n-1)\ell + \ell = n\ell$.

Case 2: Some word in P_{n-1} has length $< \ell$.

We restrict a_{n-1} so as to make all words in $\text{imC}(\alpha_{n-1})$ have length $\geq \ell$, as follows. For any $y_j \in P_{n-1}$ with $|y_j| < \ell$ we consider the finite maximal prefix code $S_j = \{0, 1\}^{\ell-|y_j|}$. We restrict a_{n-1} in such a way that y_j is replaced by $y_j \cdot S_j$, i.e., P_{n-1} becomes $(P_{n-1} - \{y_j\}) \cup y_j \cdot S_j$. Note that all words in $y_j \cdot S_j$ have length ℓ . After every word in P_{n-1} of length $< \ell$ has been replaced, let $\overline{P}_{n-1}$ be the resulting finite maximal prefix code. Now we apply the Claim in order to restrict all of $a_{n-1}, \dots, a_1$. As a result, each α_i (for $i = n-1, \dots, 1$) receives a table with words of length $\leq (n-1)\ell + \max\{|s| : s \in \bigcup_j S_j\} \leq (n-1)\ell + \ell = n\ell$. Note that in these restrictions, the length of the words in P_{n-1} only increases for the very short words (namely, words of length $< \ell$ are replaced by words of length ℓ). Hence, after restriction, the words in $\overline{P}_{n-1}$ still have length $\leq (n-1)\ell$.

Next we restrict a_n , as in case 1. Since after restriction, the words in $\overline{P}_{n-1}$ have length $\leq (n-1)\ell$, the longest word in the table of α_n has length $\leq (n-1)\ell + \ell = n\ell$. $\square$

Theorem 7.5 (1) For the elements $\varphi \in V$, the minimum size of bijective $\{0, 1, \perp\}$ -valued circuits that compute φ is polynomially related to the word length of φ in V (over $\Gamma_V \cup \{\tau_{i,i+1} : 1 \leq i\}$). More precisely, there are constants $c_1, c_2 > 0$ such that $s_\varphi \leq c_1 |\varphi|_V^2$, and $|\varphi|_V \leq c_2 s_\varphi$, where $|\varphi|_V$ is word length of $\varphi \in V$ over $\Gamma_V \cup \{\tau_{i,i+1} : 1 \leq i\}$, and s_φ is the $\{0, 1, \perp\}$ -valued bijective circuit size of φ .

(2) For the elements $\varphi \in lpV$, the minimum size of bijective binary circuits is polynomially related to the word length of φ in lpV (over $\{N, C, T\} \cup \{\tau_{i,i+1} : 1 \leq i\}$). More precisely, the word length $|\varphi|_{lpV}$ over $\{N, C, T\} \cup \{\tau_{i,i+1} : 1 \leq i\}$, and the binary circuit size b_φ of φ satisfy: $b_\varphi \leq c_1 |\varphi|_{lpV}^2$, and $|\varphi|_{lpV} \leq c_2 b_\varphi$ (for some constants $c_1, c_2 > 0$).

(3) The **distortion** function $d(\cdot)$ of lpV in V (over the generators mentioned above), and the **unpadding cost** function $u(\cdot)$ for bijective $\{0, 1, \perp\}$ -valued circuits, are polynomially related. More precisely, for some constants $c, c' > 0$ and for all $x > 0$ we have $u(x) \leq c d(cx)^2$ and $d(x) \leq c' u(c'x^2)$.

Proof. (1) For $\varphi \in V$ let s_φ be the circuit size of φ over $\Gamma_V^{\pm 1} \cup \{\tau_{i,i+1} : 1 \leq i\}$, let $|\varphi|$ be the word length over $\Gamma_V^{\pm 1} \cup \{\tau_{i,i+1} : 1 \leq i\}$.

• Proof that $s_\varphi \leq c_1 |\varphi|^2$ (for some constant $c_1 > 0$): Let $w = a_1 \dots a_n$ be a shortest word that represents φ , where $a_j \in \Gamma_V^{\pm 1} \cup \{\tau_{i,i+1} : 1 \leq i\}$ for $1 \leq j \leq n = |w| = |\varphi|$. We restrict the generators

a_j as in Lemma 7.4 so that they can be composed, and a_j will only have bitstrings of length $\leq c_1 |\varphi|$ in its table. Thus, the word w becomes a $\{0, 1, \perp\}$ -valued circuit consisting of the $n = |\varphi|$ operations a_j ($1 \leq j \leq n$), and each a_j has $\leq c_1 |\varphi|$ wires; so the circuit for φ has size $\leq c_1 |\varphi| |\varphi|$.

• Proof that $|\varphi| \leq c_2 s_\varphi$ (for some constant $c_2 > 0$): Consider any smallest bijective circuit C over $\Gamma_V^{\pm 1} \cup \{\tau_{i,i+1} : 1 \leq i\}$, of size s_φ , computing φ . This circuit is a sequence $(a_1, \dots, a_n)$ where $n = |C| = s_\varphi$. Each a_j is either of the form $\tau_{i,i+1}$, or a_j is the padding of a restriction of $(\gamma)_d$ with $d \geq 0$ and $\gamma \in \Gamma_V^{\pm 1}$. Hence, the sequence $(a_1, \dots, a_n)$ is a word of length s_φ representing φ . To obtain a word over $\Gamma_V^{\pm 1} \cup \{\tau_{i,i+1} : 1 \leq i\}$ we express the lowering operation in terms of position transpositions, as at the end of Section 5; then $(\gamma)_d$ becomes $\pi^{-1} \gamma \pi$, where π is the composition of $\leq 2m$ position transpositions of the form $\tau_{i,d+i}$ or $\tau_{i,m+i}$. Here m is the length of the longest word in any of the tables for the elements $\gamma \in \Gamma_V$; since Γ_V is fixed and finite, m is a constant. A transposition $\tau_{i,d+i}$ can be written as the composition of $< 2d$ transpositions of the form $\tau_{j,j+1}$. Let $((\gamma_j)_{d_j} : j = 1, \dots, J)$ be the list of all the lowered gates that occur in the circuit C ; then $\sum_{j=1}^J d_j < |C|$, since for each $(\gamma_j)_{d_j}$ there are d_j wires in C that are output wires of other gates (or that are inputs of C), and that are counted as part of the size of C . Thus we obtain a word of length $< c_2 s_\varphi$ (for some constant $c_2 > 0$), representing φ .

(2) The proof is very similar to the proof of (1).

(3) By (1) and (2) and by the definition of distortion we have: $c \sqrt{b_\varphi} \leq |\varphi|_{p_V} \leq d(|\varphi|_V) \leq d(c' s_\varphi)$, hence $b_\varphi \leq c'' d(c' s_\varphi)^2$. Here, c, c', c'' are constants. By the definition of the unpadding cost function it follows that $u(x) \leq c'' d(c' x)^2$.

Also by (1) and (2) and by the definition of the unpadding cost function we have: $c |\varphi|_{p_V} \leq b_\varphi \leq u(s_\varphi) \leq u(c' |\varphi|_V^2)$, hence $|\varphi|_{p_V} \leq c'' u(c' |\varphi|_V^2)$. Here, c, c', c'' are constants. By the definition of distortion it follows that $d(x) \leq c'' u(c' x^2)$. $\square$

Theorem 7.6 *Consider any element of the Thompson group F , represented by a bijection $f : P \rightarrow Q$ that preserves the dictionary order, where P and Q are finite maximal prefix codes. If f can be computed by a $\{0, 1, \perp\}$ -valued circuit of size s then $f^{-1} : Q \rightarrow P$ can be computed by a combinational circuit size $m(m+1)s + O(m^2n)$, where $m = \max\{|p| : p \in P\}$ and $n = \max\{|q| : q \in Q\}$.*

Moreover, a circuit for f^{-1} can be found from a circuit for f deterministically in polynomial time in terms of s, m, n .

Proof. Suppose $f^\perp(x \perp^{m-|x|}) = y \perp^{n-|y|}$, and $y \perp^{n-|y|}$ is given. The idea for inverting $f^\perp$ is simple: Since f preserves the dictionary order we can find $x \perp^{m-|x|}$ by adapting the classical *binary search* algorithm. This algorithm is usually used for searching in a sorted array; but it works in a similar way for inverting any order-preserving map.

A few technical details have to be discussed before we give an algorithm for inverting $f^\perp$. For many strings $z \in \{0, 1, \perp\}^n$ there is no inverse image under $f^\perp$; in that case our inversion algorithm will output $\perp^m$. For example, $z \notin \{0, 1\}^* \perp^*$ has no inverse. Also, since the range of $f^\perp$ is $Q^\perp \cup \{\perp^n\}$ where Q is a finite maximal prefix code we have: If $y \perp^{n-|y|}$ has an inverse then there is no inverse for any strict prefix of y ; i.e., if $w \in \{0, 1\}^*$ is a strict prefix of y then $w \perp^{n-|w|}$ has no inverse. On the other hand, for every $v \in \{0, 1\}^n$, there exists exactly one prefix y of v such that $y \perp^{n-|y|}$ has an inverse. Similarly, for every $u \in \{0, 1\}^m$, there exists exactly one prefix x of u such that $f^\perp(x \perp^{m-|x|}) \neq \perp^n$.

The binary search can be pictured on the complete binary tree with vertex set $\{0, 1\}^{\leq m}$, with root ε (the empty word), and leaves $\{0, 1\}^m$; the children of a vertex $v \in \{0, 1\}^{\leq m}$ are $v0$ and $v1$. The search uses a variable vertex v , initialized to ε , and proceeds from v to $v0$ or $v1$, until success, or until v becomes a leaf.

Algorithm (for inverting $f^\perp$)

For any input $z \in \{0, 1, \perp\}^n$ it is easy to check whether $z \notin \{0, 1\}^* \perp^*$; in that case the output is $\perp^m$. Assume from now on that the input is of the form $y \perp^{n-|y|}$, with $y \in \{0, 1\}^*$, $|y| \leq n$. Let $v \in \{0, 1\}^{\leq m}$ be a bitstring, initialized to $v = \varepsilon$ (the empty string). Below, $<_d$ and $>_d$ refer to the dictionary order.

repeat the following until the exit command

begin

find the prefix x of $v 1 0^{m-1-|v|}$ (if $|v| < m$) or the prefix x of v (if $|v| = m$), such that

$f^\perp(x \perp^{m-|x|}) \neq \perp^n$ (this is done by trying all prefixes of $v 1 0^{m-1-|v|}$, respectively of v);

if $f^\perp(x \perp^{m-|x|}) = y \perp^{n-|y|}$ **then** return $x \perp^{m-|x|}$ as output, and **exit**;

if $|v| = m$ **then** return $\perp^m$ as output, and **exit**;

if $f^\perp(x \perp^{m-|x|}) <_d y \perp^{n-|y|}$ and $|v| < m$ **then** replace v by $v1$;

else (i.e., when $f^\perp(x \perp^{m-|x|}) >_d y \perp^{n-|y|}$ and $|v| < m$) replace v by $v0$;

end (of repeat loop);

end (of algorithm).

Let us show that this program can be implemented by an acyclic circuit of size $m(m+1)s + O(m^2n)$. The loop of the program is executed at most m times, and each execution of the loop will be implemented as one of m stages of the complete circuit.

Each execution of the loop takes at most $(m+1)s + O(mn)$ gates.

The first part of the loop (namely, to “find the prefix x ”) requires m copies of the circuit of $f^\perp$, each of which is followed by $O(n)$ gates to check equality with $\perp^n$, followed by a tree of n AND-gates. Moreover, recall that when we want to apply the same type of gate to different variables (wires) we need to permute wires (using bit position transpositions $\tau_{i,j}$). Similarly, permutations may need to be applied to the output wires of a gate. This adds at most a constant number of operations for each gate. So the first part of the loop uses $ms + O(mn)$ gates.

The first **if** condition requires another copy of the circuit of $f^\perp$, followed by $O(n)$ gates to compare the result with $y \perp^{n-|y|}$ for equality and to check for $<_d$ or $>_d$ in the dictionary order. The $<_d$ - or $>_d$ -comparison of two strings of the same length can be done by a finite automaton, reading both strings in parallel from left to right; if the inputs are restricted to strings of length n , this automaton can then be turned into a *prefix circuit* (of Ladner and Fischer [18]). The Ladner-Fischer circuit consists of $\leq 4n$ copies of a gate that implements the (fixed) transition function of the finite automaton. The prefix circuit uses fan-out $< n$; however, there is also a bounded-fan-out design for the prefix circuit, using just $< 9n$ gates (see p. 205 of [19]). Moreover, applying the same gate to different variables first requires some permutations of wires; this introduces a constant factor (since gates have a fixed number of input-output wires, so only a fixed number of wires are permuted back and forth). Checking whether $|v| = m$ is equivalent to checking absence of $\perp$, which requires $O(n)$ gates. So overall the **if**-statements require $s + O(n)$ gates.

Finally, the above description amounts to a polynomial-time procedure for producing the circuit that implements $(f^\perp)^{-1}$. $\square$

As a consequence, $(f^\perp)^{-1}$ is not much harder to compute than $f^\perp$ itself. So, without need to define the concept of a one-way function in detail we can conclude that for any reasonable definition of “one-way function” we have:

Corollary 7.7 *The Thompson group F does not contain any one-way functions.*

Recall that in our algorithm for finding the $lpV \cdot F$ factorization of $\varphi \in V$, the element φ is first restricted so as to make $\text{imC}(\varphi) = \{0, 1\}^n$. We will show next that this restriction does not increase

circuit complexity much, and that we can find a circuit for certain restrictions. On the other hand, we saw in Theorem 7.12(3) that the opposite operation, namely finding the maximal extension, is hard.

Lemma 7.8 *Every $\varphi \in V$ has a restriction Φ such that $\text{imC}(\Phi) = \{0, 1\}^n$, and such that the circuit size of Φ is only polynomially larger than the circuit size of φ .*

More precisely, assume $\varphi^\perp$ has a circuit of size s , with m input variables and n output variables (over $\{0, 1, \perp\}$). Then the restriction Φ with $\text{imC}(\Phi) = \{0, 1\}^n$ has a circuit of size $\leq 4s(n + m + 1)$, with $n + m$ input variables and n output variables. Moreover, such a circuit for $\Phi^\perp$ can be found from the given circuit for $\varphi^\perp$ deterministically in polynomial time (as a function of s, m, n); i.e., there is a polynomial-time reduction from the problem of finding a circuit for Φ to the problem of finding a circuit for φ (for $\{0, 1, \perp\}$ -valued circuits).

Proof. We can view φ as a bijection $P \rightarrow Q$ where $P, Q \subset \{0, 1\}^*$ are finite maximal prefix codes. Since the circuit for $\varphi^\perp$ has n output variables, we have $n = \max\{|y| : y \in Q\}$. Let $\Phi : P_1 \rightarrow \{0, 1\}^n$ be the restriction of φ with image code $\{0, 1\}^n$, where P_1 is the finite maximal prefix code obtained when φ is restricted to make the image code $\{0, 1\}^n$. Let $m = \max\{|x| : x \in P\}$. Thus, all words in the finite maximal prefix code P_1 have length $\leq n + m$. We now construct a $\{0, 1, \perp\}$ -valued circuit for $\Phi^\perp$, with $n + m$ input variables and n output variables. On an input $x \in \{0, 1, \perp\}^{n+m}$ the circuit behaves as follows:

- If $x \notin \{0, 1\}^* \perp^*$, the output is $\Phi(x) = \perp^n$.

To check whether $x \notin \{0, 1\}^* \perp^*$ we consider all $n + m - 1$ pairs (x_i, x_{i+1}) of neighboring input variables (for $i = 1, \dots, n + m - 1$) and check whether any of them have values $(x_i, x_{i+1}) = (\perp, 0)$ or $(\perp, 1)$, using $n + m - 1$ gates. To produce the output $\perp^n$ in that case, the $n + m - 1$ gates above feed into a tree of OR gates whose output is 1 iff $(\perp, 0)$ or $(\perp, 1)$ occurs anywhere in input pairs. The OR-tree and the output $\perp^n$ require $< 2(n + m)$ gates. Thus so far we have $< 3(n + m)$ gates in total.

- If $x \in \{0, 1\}^* \perp^*$, since $\Phi^\perp$ has $m + n$ input wires, we write $x = u \perp^i$ with $u \in \{0, 1\}^{n+m-i}$. We look at each prefix p of $u = pz$, in order of increasing length $|p| = 0, 1, \dots, m + n - i$, and feed $p \perp^{m-|p|}$ into $\varphi^\perp$.

- If $\varphi^\perp(p \perp^{m-|p|}) = \perp^n$, we ignore p and look at the next prefix of u .

- If $\varphi^\perp(p \perp^{m-|p|}) = q \perp^{m-|q|}$ for some $q \in \{0, 1\}^*$, we conclude that $\varphi(p) = q$ and $\varphi(u) = \varphi(pz) = qz$. Hence, if $|z| = n - |q|$ we produce the output $\Phi(u \perp^i) = qz \in \{0, 1\}^n$; so Φ agrees with φ and has $\text{imC}(\Phi) = \{0, 1\}^n$. If $|z| \neq n - |q|$ we produce the output $\Phi(u \perp^i) = \perp^n$. (No new prefixes of u will be considered.)

In the above construction, the circuit of $\varphi^\perp$ is repeated $m + n + 1$ times, since an input of length $m + n$ has $\leq m + n + 1$ prefixes. So this part of the circuit has size $s(m + n + 1)$. We need another $3n(m + n + 1)$ gates to combine the outputs of the $(m + n + 1)$ copies of the $\varphi^\perp$ -circuit: If one of the $\varphi^\perp$ -circuits produces an output in $\{0, 1\}^n$, that output has to be the final output; if all the copies of the $\varphi^\perp$ -circuit produce $\perp^n$, then $\perp^n$ should be the final output.

Finally, the total circuit for $\Phi^\perp$ has size $\leq 3(n + m) + s(m + n + 1) + 3n(m + n + 1) \leq (s + 3n + 3)(m + n + 1) \leq 4s(m + n + 1)$ (the last " $\leq$ " holds since $s \geq m + n$ and $m, n \geq 1$). The above description of the construction of a circuit for $\Phi^\perp$ is a deterministic algorithm whose running time is a polynomial in s . $\square$

An immediate consequence of Lemma 7.8 is the following:

Corollary 7.9 *Assume $f \in F$ has a $\{0, 1, \perp\}$ -valued circuit of size $\leq s$, with m input variables and n output variables. Then the restriction of f with $\text{imC}(f) = \{0, 1\}^n$, i.e., the restriction of f that makes f a rank function $\text{rank}_P(\cdot)$, has a $\{0, 1, \perp\}$ -valued circuit of size $\leq 4s(m + n + 1)$.*

In other words, representing elements of F by rank functions does not lead to a large increase in circuit complexity.

Proposition 7.10 *Let φ be an element of the Thompson group V , and let $\varphi = \pi \cdot f$ be its $lpV \cdot F$ factorization. Let $\varphi : P \rightarrow \{0, 1\}^n$ be a representation of φ by a bijection from a finite maximal prefix code $P \subseteq \{0, 1\}^{\leq m}$ onto $\{0, 1\}^n$. Suppose that the rank function of P can be computed by a circuit of size $\leq s$.*

Then f has circuit complexity $\leq s$, and the circuit complexities of φ and of π differ by at most $m(m+1)s + O(m^2n)$. The circuit complexities of φ^{-1} and π^{-1} differ by at most s .

Moreover, the circuits for f and π can be found in deterministic polynomial time.

Proof. We apply our $lpV \cdot F$ factorization algorithm. Since φ already has $\text{imC}(\varphi) = \{0, 1\}^n$, we have $f = \text{rank}_P(\cdot)$, and hence by assumption, f has circuit complexity $\leq s$.

To obtain a circuit for $\pi = \varphi f^{-1}$ we use Theorem 7.6 to obtain a circuit for f^{-1} of size $\leq m(m+1)s + O(m^2n)$, where $m = \max\{|p| : p \in P\}$; then we compose the circuit for f^{-1} with the circuit for φ .

To obtain a circuit for $\varphi = \pi \cdot f$ from a circuit for π we just compose the circuit for f and the circuit for π . $\square$

A consequence of Proposition 7.10 is the following. If an element of V has a representation $\varphi : P \rightarrow \{0, 1\}^n$ (for some $n > 0$), and if P is a finite maximal prefix code with easy rank function, then φ and of π have similar circuit complexities; φ^{-1} and π^{-1} also have similar circuit complexities. Thus we have:

Corollary 7.11 *If there exists a one-way bijection $\varphi : P \rightarrow \{0, 1\}^n$ (for some $n > 0$), where P is a finite maximal prefix code with easy rank function, then there exists a one-way permutation π of $\{0, 1\}^n$.*

7.2 coNP-complete and $\#\mathcal{P}$ -complete problems in the Thompson groups

The following coNP-completeness results are similar to the well-known coNP-completeness of questions about circuits, except that here we deal with circuits that compute bijections, in the sense defined at the beginning of this section.

Theorem 7.12 *The following decision problems are coNP-complete:*

- (1) *Given two $\{0, 1, \perp\}$ -valued bijective circuits, do they compute the same element of V ?*
- (2) *Given two $\{0, 1, \perp\}$ -valued bijective circuits for computing elements $\psi, \varphi \in V$, is ψ the maximal extension of φ ?*
- (3) *Given a $\{0, 1, \perp\}$ -valued bijective circuit, does it compute the identity element of V ?*

The problems remain coNP-complete when the given $\{0, 1, \perp\}$ -valued circuits are general (not necessarily bijective).

Proof. Let us first check that these problems are in coNP. Problems (1), (3) and (4) are variants of the classical circuit equivalence problem. For problem (2), we can check in coNP whether ψ and φ represent the same element of V . To check in NP whether ψ is *not* maximally extended, guess entries $(x_0, y_0), (x_1, y_1)$ in the table of ψ ; the lengths of x and y are no larger than the size of the given circuit for ψ , and the fact that (x_0, y_0) and (x_1, y_1) are in the table of ψ can be checked rapidly using the circuit for ψ .

Hardness: Problem (3) is a special case of (2) and of (1) (letting ψ be the identity map with domain and image codes consisting of just the empty word), so (2) and (1) are at least as hard as (3).

The hardness of (3) is a consequence of the fact that the word problem of $G_{3,1}$ over the generating set $\Gamma_{3,1} \cup \{\tau_{i,j} : 1 \leq i < j\}$ is coNP-complete (proved in [3]), and the fact (proved in Theorem 7.5) that every word over $\Gamma_{3,1} \cup \{\tau_{i,j} : 1 \leq i < j\}$ has a $\{0, 1, \perp\}$ -valued circuit whose size is linearly bounded by the size of the word. $\square$

Proposition 7.10 shows that under certain conditions the $lpV \cdot F$ factorization is easy to find. The next Theorems show that in general, finding the $lpV \cdot F$ factorization is $\#P$ -hard, even when circuits for the rank functions of the domain code and image code are given.

To define the class $\#P$ we consider functions of the form $f : A^* \rightarrow \{0, 1\}^*$, where A is a finite alphabet, and elements of $\{0, 1\}^*$ are interpreted as non-negative integers in binary representation. Intuitively, for a function f in $\#P$ and for $x \in A^*$, $f(x)$ is the number of ways a relation that is parameterized by x can be satisfied. More precisely we will use the following definition of the $\#P$; see e.g. [28].

Definition 7.13 *A function $f : A^* \rightarrow \{0, 1\}^*$ is in $\#P$ iff there is a relation $R \subseteq A^* \times B^*$ (where B is a finite alphabet) such that*

- (1) *for all $x \in A^*$: $f(x) = |\{w \in B^* : (x, w) \in R\}|$, with $f(x) \in \{0, 1\}^*$ interpreted as an integer;*
- (2) *R is in $\mathcal{P}$ (deterministic polynomial time);*
- (3) *R is polynomially balanced (also called “polynomially honest”); i.e., there is a polynomial $p(\cdot)$ such that for all $(x, w) \in R$, $|x| \leq p(|w|)$ and $|w| \leq p(|x|)$.*

Theorem 7.14 (Ranking problem for finite maximal prefix codes)

The following problem is $\#P$ -complete.

Input: *A $\{0, 1, \perp\}$ -valued circuit that accepts a finite maximal prefix code $P \subset \{0, 1\}^*$, and $x \in P$.*

Output: *The rank of x in P according to dictionary order.*

Proof. The problem is clearly in $\#P$ since $\text{rank}_P(x)$ is the number of words $w \in B^*$ (here $B = \{0, 1\}$) satisfying the relation “ $w \in P$ and $w <_d x$ ”. Moreover, the prefix code P is given by a circuit, whose size is counted as part of the input size of the problem, so the relation “ $w \in P$ and $w <_d x$ ” can be verified in deterministic polynomial time.

Next, we will reduce the $\#P$ -complete problem $\#SAT$ to our problem. For a boolean formula $\beta(x_1, \dots, x_n)$ with n boolean variables, let $T \subseteq \{0, 1\}^n$ be the set of truth-value assignments that make β true. Although T is a finite prefix code, T is not maximal, and the cardinality $|T|$ is not necessarily a power of 2; however, finding $|T|$, given β , is precisely the $\#P$ -complete problem $\#SAT$. We will use T to construct a finite maximal prefix code P (with $|P|$ a power of 2), whose ranking function determines $|T|$. We use the notation $\overline{T} = \{0, 1\}^n - T$. Let

$$P_T = 00\overline{T} \cup 00T0 \cup 00T1 \cup 01\{0, 1\}^n \cup 1T \cup 1\overline{T}0 \cup 1\overline{T}1.$$

Then P_T is a finite maximal prefix code of cardinality $|P_T| = 2^{n+2}$. Membership in P_T is easily decided by the formula β .

Finally, $|T|$ is easily derived from the rank of 001^n or of 001^n1 in P_T . Indeed, if $1^n \in \overline{T}$ then $\text{rank}_{P_T}(001^n) + 1 = |T| \cdot 2 + |\overline{T}| = |T| + 2^n$; if $1^n \in T$ then $\text{rank}_{P_T}(001^n1) + 1 = |T| + 2^n$. Hence, $|T|$ can easily be obtained from $\text{rank}_{P_T}(01^n)$ or $\text{rank}_{P_T}(01^n1)$; the numbers are written in binary, so the representation of 2^n is not large. $\square$

Theorem 7.15 ($lpV \cdot F$ factorization problem, given $\Phi : P \rightarrow \{0, 1\}^n$)

The following problem is $\#P$ -complete.

Input: *A $\{0, 1, \perp\}$ -valued circuit that computes a bijection $\Phi : P \rightarrow \{0, 1\}^n$ (where P is a finite maximal prefix code over $\{0, 1\}$), and $x \in P$.*

Output: The rank of x in P according to dictionary order. (Recall that $\text{rank}_P(\cdot)$ is the F -part in the $\text{lpV} \cdot F$ factorization of Φ .)

The problem remains $\#\mathcal{P}$ -complete if we assume that circuits for both Φ and Φ^{-1} are given. Also, evaluating π or π^{-1} is $\#\mathcal{P}$ -complete (where $\Phi(\cdot) = \pi f(\cdot)$ is the $\text{lpV} \cdot F$ factorization).

Proof: The problem is in $\#\mathcal{P}$ because the circuit for Φ can also be used to test membership in P . To show $\#\mathcal{P}$ -hardness, let P_T be as in Theorem 7.14 above, where $T \subseteq \{0, 1\}^n$ is the set of truth value assignments that make a given boolean formula β true; again, $\bar{T}$ denotes $\{0, 1\}^n - T$.

$$P_T = 00\bar{T} \cup 00T0 \cup 00T1 \cup 01\{0, 1\}^n \cup 1T \cup 1\bar{T}0 \cup 1\bar{T}1.$$

Let $\Phi : P_T \rightarrow \{0, 1\}^{n+2}$ be the bijection defined as follows for all $x \in \{0, 1\}^n$:

$$\begin{aligned} 00x &\in 00\bar{T} \mapsto 11x \in 11\bar{T} \\ 00x0 &\in 00T0 \mapsto 0x0 \in 0T0 \\ 00x1 &\in 00T1 \mapsto 0x1 \in 0T1 \\ 01x &\in 01\{0, 1\}^n \mapsto 10x \in 10\{0, 1\}^n \\ 1x0 &\in 1\bar{T}0 \mapsto 0x0 \in 0\bar{T}0 \\ 1x1 &\in 1\bar{T}1 \mapsto 0x1 \in 0\bar{T}1 \\ 1x &\in 1T \mapsto 11x \in 11T. \end{aligned}$$

Clearly Φ and Φ^{-1} can easily be computed from the boolean formula β , and they have small circuits that can be derived from the boolean formula β .

Let $\Phi = \pi f$ be the $\text{lpV} \cdot F$ factorization of Φ ; then $f = \text{rank}_{P_T}(\cdot)$. We saw in Theorem 7.14 above that evaluating $\text{rank}_{P_T}(\cdot)$ is a $\#\mathcal{P}$ -complete problem. Thus by the reduction of f to f^{-1} in Theorem 7.6, the problem of computing f^{-1} is also $\#\mathcal{P}$ -complete.

To show that the evaluations of π and π^{-1} are $\#\mathcal{P}$ -hard, note that $f = \pi^{-1}\Phi$ and $f^{-1} = \Phi^{-1}\pi$; since Φ and Φ^{-1} are easy to evaluate, this reduces the $\#\mathcal{P}$ -complete evaluation problems for f and f^{-1} to the evaluation of π^{-1} , respectively π . $\square$

The above Theorem means that ranking in P_T according to the dictionary order is hard, but there may exist another bijection $P_T \rightarrow \{0, 1\}^n$, namely Φ , which provides an easy ranking in P_T .

Theorem 7.16 (*lpV · F factorization, given $\varphi : P_0 \rightarrow Q_0$, $\text{rank}_{P_0}(\cdot)$ and $\text{rank}_{Q_0}(\cdot)$*)

The following problem is $\#\mathcal{P}$ -complete.

Input, consisting of three parts:

- A $\{0, 1, \perp\}$ -valued circuit that computes a bijection $\varphi : P_0 \rightarrow Q_0$ (where P_0 and Q_0 are finite maximal prefix codes over $\{0, 1\}$),
- two $\{0, 1, \perp\}$ -valued circuits that compute the rank functions of P_0 , respectively Q_0 ,
- and $x \in P_1$ (where P_1 is the domain code that φ receives when it is restricted so as to have $\text{im}C(\varphi) = \{0, 1\}^n$, where $n = \max\{|q| : q \in Q_0\}$).

Output: The rank of x in P_1 according to dictionary order.

The problems remains $\#\mathcal{P}$ -complete if we assume that circuits for both φ and φ^{-1} are given.

Also, evaluating π or π^{-1} is $\#\mathcal{P}$ -complete (where $\varphi = \pi f$ be the $\text{lpV} \cdot F$ factorization).

Proof: The problem is in $\#\mathcal{P}$ because the circuit for φ can also be used to obtain a circuit for the restriction $P_1 \rightarrow \{0, 1\}^n$ of φ , by Lemma 7.8; this circuit can then be used to test membership in P_1 .

To show $\#\mathcal{P}$ -hardness, let T and P_T be as in the proofs of Theorems 7.14 and 7.16. Let

$$P_0 = \{00, 01, 1\} \cdot \{0, 1\}^n = 00T \cup 00\bar{T} \cup 01\{0, 1\}^n \cup 1T \cup 1\bar{T},$$

$$Q_0 = \{0, 10, 11\} \cdot \{0, 1\}^n = 0T \cup 0\overline{T} \cup 10\{0, 1\}^n \cup 11T \cup 11\overline{T},$$

and define $\varphi : P_0 \rightarrow Q_0$ by

$$00x \in 00\overline{T} \mapsto 11x \in 11\overline{T}$$

$$00x \in 00T \mapsto 0x \in 0T$$

$$01x \in 01\{0, 1\}^n \mapsto 10x \in 10\{0, 1\}^n$$

$$1x \in 1\overline{T} \mapsto 0x \in 0\overline{T}.$$

$$1x \in 1T \mapsto 11x \in 11T$$

Then φ , $\text{rank}_{P_0}(\cdot)$, and $\text{rank}_{Q_0}(\cdot)$, and their inverses have small circuits, that are easily derived from the boolean formula β .

Next, we restrict φ in such a way that its image code becomes $\{0, 1\}^{n+2}$. The resulting bijection is exactly the bijection $\Phi : P_T \rightarrow \{0, 1\}^{n+2}$ of the proof of Theorem 7.15. All the claimed conclusions of Theorem 7.16 now follow from Theorem 7.15. $\square$

The above $\#\mathcal{P}$ -completeness results imply that finding circuits for the $lpV \cdot F$ factors π, f of $\varphi \in V$ is difficult (if $\mathcal{P} \neq NP$, etc.). However, whether this implies that the factors require large circuits remains a very difficult open problem.

References

- [1] J.C. Birget, “Computational asymmetry and distortion”, (in progress).
- [2] J.C. Birget, “The groups of Richard Thompson and complexity”, *International J. of Algebra and Computation* 14(5,6) (Dec. 2004) 569-626 (Mathematics ArXiv math.GR/0204292, Apr. 2002).
- [3] J.C. Birget, “Circuits, coNP-completeness, and the groups of Richard Thompson”, *International J. of Algebra and Computation*, 16(1) (Feb. 2006) 35-90 (Mathematics ArXiv math.GR/0310335, Oct. 2003).
- [4] M. Brin, C. Squier, “Groups of piecewise linear homeomorphisms of the real line”, *Inventiones Mathematicae* 79 (1985) 485-498.
- [5] M. Brin, “The Chameleon Groups of Richard J. Thompson: Automorphisms and Dynamics”, *Publications Math. de l’IHES* 84 (1997) 5-33.
- [6] M. Brin, “The ubiquity of Thompson’s group F in groups of piecewise linear homeomorphisms of the unit interval”, *J. London Mathematical Society (2)*, 60 (1999) 449-460.
- [7] K.S. Brown, R. Geoghegan, “An infinite-dimensional torsion-free FP_∞ group”, *Inventiones Mathematicae* 77 (1984) 367-381.
- [8] J. Burillo, S. Cleary, M. Stein, J. Taback, “Combinatorial and metric properties of Thompson’s group T ”, Mathematics ArXiv math.GR/0503670; to appear in *Transactions of the AMS*.
- [9] J. W. Cannon, W. J. Floyd, W. R. Parry, “Introductory notes on Richard Thompson’s groups”, *L’Enseignement Mathématique* 42 (1996) 215-256.
- [10] S. Cleary, J. Taback, “Combinatorial properties of Thompson’s group F ”, *Transactions of the American Mathematical Society*, 356(7) (2004) 2825-2849.

- [11] P. Dehornoy, “Geometric presentations for Thompson’s groups”, *J. of Pure and Applied Algebra* 203 (2005) 1-44.
- [12] E. Fredkin, T. Toffoli, “Conservative logic”, *International J. Theoretical Physics* 21 (1982) 219-253.
- [13] E. Ghys, V. Sergiescu, “Sur un groupe remarquable de difféomorphismes du cercle”, *Commentarii Mathematici Helvetici* 62(2) (1987) 185-239.
- [14] V. Guba, M.V. Sapir, “Diagram groups”, *Memoirs American Math. Soc.*, 130 no. 620 (1997), viii+117 pages.
- [15] B. Hartley, “Simple locally finite groups”, in *Finite and Locally Finite Groups*, B. Hartley, G.M. Seitz, A.V. Borovik, and R.M. Bryant (editors), Kuwer Academic Publishers (1995).
- [16] G. Higman, “Finitely presented infinite simple groups”, Notes on Pure Mathematics 8, The Australian National University, Canberra (1974).
- [17] O.H. Kegel, B.A.F. Wehrfritz, *Locally Finite Groups*, North-Holland Publ. Co., Amsterdam (1973).
- [18] R.E. Ladner, M.J. Fischer, “Parallel prefix computation”, *Journal of the ACM* 27 (1980) 831-838.
- [19] S. Lakshmivarahan, S. Dhall, *Parallel Computing Using the Prefix Problem*, Oxford University Press (1994).
- [20] R. McKenzie, R. J. Thompson, “An elementary construction of unsolvable word problems in group theory”, in *Word Problems*, (W. W. Boone, F. B. Cannonito, R. C. Lyndon, editors), North-Holland (1973) pp. 457-478.
- [21] V.V. Nekrashevych, “Cuntz-Pimsner algebras of group actions”, *J. Operator Theory* 52(2) (2004) 223-249.
- [22] Elizabeth A. Scott, “A construction which can be used to produce finitely presented infinite simple groups”, *J. of Algebra* 90 (1984) 294-322.
- [23] V. Shende, A. Prasad, I. Markov, J. Hayes, “Synthesis of reversible logic circuits”. *IEEE Transactions on Computer-Aided Design of Integrated Circuits and Systems* 22(6) (2003) 710-722.
- [24] Richard J. Thompson, Manuscript (1960s).
- [25] Richard J. Thompson, “Embeddings into finitely generated simple groups which preserve the word problem”, in *Word Problems II*, (S. Adian, W. Boone, G. Higman, editors), North-Holland (1980) pp. 401-441.
- [26] T. Toffoli, “Reversible computing”, MIT Laboratory for Computer Science, Technical Memo MIT/LCS/TM-151 (1980).
- [27] T. Toffoli, “Reversible computing”, *Automata, Languages and Programming* (7th Colloquium), Lecture Notes in Computer Science 85 (July 1980) 623-644. (Abridged version of [26].)
- [28] J. van Leeuwen (editor), *Handbook of Theoretical Computer Science*, volume **A**, MIT Press and Elsevier (1990).

- [29] I. Wegener, *The complexity of boolean functions*, Wiley/Teubner (1987).
- [30] A.E. Zalesskii, “Group rings of inductive limits of alternating groups”, *Algebra and Analysis* 2 (1990) 132-149 (in Russian). English Translation: *Leningrad Math. J.* 2 (1991) 1287-1303.

Jean-Camille Birget
Dept. of Computer Science
Rutgers University at Camden
Camden, NJ 08102, USA
`birget@camden.rutgers.edu`